

**Works Approval Number**

W5865/2015/1

Number/Year issued/Version (for amendments or renewals)

**Works Approval Holder**

GD Pork Pty Ltd

126 978 676

Full legal name

ACN Number

**Registered business address**

Level 3, 35 Outram Street  
WEST PERTH WA 6005

**Address for notifications**

If different to registered address

38 Victoria Circle  
GREENFIELDS WA 6210

**Duration**

Original works approval term or renewal period

28 September 2015 to 27 September 2018

Commencement date

Expiry date

**Prescribed Premises**

Category 2 Intensive piggery: premises on which pigs are fed, watered and housed in pens

Category Number of Prescribed Premises and description

27,360 animals (28,368 Standard Pig Units (SPU))

Production/Design Capacity

**Premises**

Lot 10 on Plan 23562  
Certificate of Title Volume 2173 Folio 889  
Corner of Albany Highway and Crapella Road  
BOSCABEL WA 6394

Legal description

**Amendment**

First Issue

Effective date

This Works Approval is granted in respect of Works to be constructed on the Premises, subject to conditions, to the Works Approval Holder on 28 September 2015 by:

---

Kelly Faulkner

Executive Director Licensing and Approvals

*an officer delegated under section 20 of the Environmental Protection Act 1986 (WA)*

## Premises Description

The Premises are located at Lot 10 Crapella Road, Boscabel WA 6394.

The Works Approval Holder is carrying out activities at the Premises which fall within Category 2, and are Prescribed Premises under the *Environmental Protection Act 1986* (EP Act). On completion of the Works, the Works Approval Holder will operate an intensive piggery comprising:

- Nine tunnel/curtain ventilated finisher piggery sheds;
- 36 extensive deep litter sheds;
- Waste treatment plant consisting of a feed tank, enclosed digester, and biogas reuse system (engines and flare);
- An evaporation pond with two compartments (33,725 m<sup>3</sup>; lined with clay);
- Stormwater detention basins; and
- Silos, liquid feed shed facilities, feed mill;

## Conditions

### Environmental compliance

1. The Works Approval Holder must comply with the EP Act and all regulations prescribed under the EP Act applicable to the Premises, including:
  - (a) the duties of an occupier under section 61;
  - (b) the duty to notify the CEO of discharges of waste under section 72; and
  - (c) not causing, or doing anything that is likely to cause, an offence under the EP Act, except where the Works Approval Holder does something in accordance with a Condition which expressly states that a defence under section 74A of the EP Act may be available.

### Premises

2. The Works Approval Holder must carry out the Works within the Premises in accordance with the requirements set out in Schedule 2.
3. This Works Approval applies to the Premises defined in the Premises Description Table, and as depicted in the Premises Map in Schedule 1.

Premises Description	
General Location	Legal land description, reserve or tenement (all or part)
Lot 10 Crapella Road BOSCABEL WA 6394	Lot 10 on Plan 23562 Certificate of Title Volume 2173 Folio 889

### Location of Works

4. The Works Approval Holder must locate the Works generally in accordance with the Site Plans in Schedule 3.

### Infrastructure Requirements

5. Subject to Condition 7, at least 10 business days prior to the commencement of the Works, the Works Approval Holder must provide to the CEO engineering or building certification from a suitably qualified professional confirming that the detailed construction drawings and plans for the Works include each item of infrastructure or component of infrastructure specified in column 1 with the requirements specified in column 2, as set out in the Infrastructure Requirements Table below.

6. Subject to Condition 7, on completion of the Works, the Works Approval Holder must provide to the CEO engineering or building certification from a suitably qualified professional confirming each item of infrastructure or component of infrastructure specified in column 1 with the requirements specified in column 2, as set out in the Infrastructure Requirements Table below have been constructed with no material defects.
7. The Works Approval Holder must not depart from the requirements specified in column 2 of the Infrastructure Requirements Table except:
- (a) where such departure does is minor in nature and does not materially change or affect the infrastructure; or
  - (b) where such departure improves the functionality of the infrastructure and does not increase risks to public health, public amenity or the environment;
- and all other Conditions in this Works Approval are still satisfied.
8. If Condition 7 applies, then the Works Approval Holder must provide the CEO with a list of departures which are certified as complying with Condition 7 at the same times, and from the same professional, as the certifications under Conditions 5 and 6.

Infrastructure Requirements Table	
Column 1	Column 2
Infrastructure	Requirements (design and construction)
All	The evaporation pond and piggery infrastructure (with the exception of stormwater dams) must be located at least 50m from geomorphic wetlands. <i>The distance from infrastructure must be calculated from the outer perimeter of any embankment or physical building.</i>
Finisher Sheds	The wastewater treatment system must be designed and constructed so as to meet the following specifications: <ul style="list-style-type: none"> <li>(a) Finisher sheds must comprise slatted concrete floors and contain continuous feeding system to all animals within the shed.</li> <li>(b) Employ pull and plug systems for all finisher sheds, as described in the Environment Management Plan, comprising of impermeable, corrosion resistant and sturdy underfloor pits and covered concrete collection sump.</li> <li>(c) Ensure all wastewater and slurry from the intensive piggery sheds is directed to the wastewater treatment plant by 300mm diameter impermeable PVC piping.</li> <li>(d) Ensure all waste storage and treatment areas are constructed from impermeable concrete hardstand.</li> </ul>
Waste Treatment Plant	Following construction and commissioning of the Waste Treatment Plant certification must be provided from a suitably qualified professional that: <ul style="list-style-type: none"> <li>(a) the plant has no major operational defects; and</li> <li>(b) is fit for the purpose intended being the treatment of waste from the maximum number of SPUs to be held on the premises.</li> </ul>

Infrastructure Requirements Table	
Column 1	Column 2
Infrastructure	Requirements (design and construction)
Evaporation Pond	<p>(a) The evaporation pond must have a minimum 2m separation to groundwater.</p> <p>(b) Exact distances to groundwater must be certified prior to commencement of construction.</p> <p><i>Separation to groundwater refers to the vertical separation of the infrastructure calculated from the underside of the lowest point to the highest point of the highest seasonal water table.</i></p> <p>(a) The evaporation pond to be constructed in accordance with the documentation provided through the application and supporting documentation and to meet the following specifications:</p> <ul style="list-style-type: none"> <li>(i) minimum internal capacity of 33,725 m<sup>3</sup>;</li> <li>(ii) minimum surface area of 36,000 m<sup>2</sup>;</li> <li>(iii) minimum length at crest of 360 m;</li> <li>(iv) minimum width at crest of 100 m;</li> <li>(v) internal batter not exceeding 1:2.5 (horizontal:vertical); and</li> <li>(vi) maximum water depth of 1m (not including freeboard).</li> </ul> <p>(b) Soils used for the lining of the evaporation pond must be free from plant roots and reactive, soluble and organic matter.</p> <p>(c) The liner material used for the evaporation pond must meet the following criteria:</p> <ul style="list-style-type: none"> <li>(i) percentage fines with acceptability of: <ul style="list-style-type: none"> <li>(a) more than 25 per cent passing a 75 micron sieve; and</li> <li>(b) more than 15 per cent passing a 2 micron sieve,</li> </ul> tested using AS 1289 3.6.1-2009 </li> <li>(ii) liquid limit with acceptability of 30 to 70 per cent tested using AS 1289 3.1.2-2009.</li> <li>(iii) plasticity index with acceptability of more than 15, tested using method AS 1289 3.3.1-2009.</li> <li>(iv) Emerson class number with acceptability of 5 to 6 tested using AS 1289 3.8.1-2006.</li> </ul> <p>(d) The liner material must be homogeneous in nature and properties, with no sandy patches exceeding the liner specification or rocks retained on a 37.5 mm sieve.</p> <p>(e) The liner must be installed in at least two layers of equal thickness to ensure adequate compaction is achieved and be moisture-conditioned to achieve the maximum design soil density exceeding the 95 per cent maximum (in place) dry density (MDD) determined using AS 1289.5.2.1 (2003) and AS 1289 5.4.1 (2007).</p> <p>(f) The minimum thickness of the compacted soil liner should be 300 mm with a tolerance of 5 mm.</p> <p>(g) The compacted liner must uniformly cover both the base and perimeter of the pond to achieve one integrated holding pond.</p> <p>(h) The construction of the lined pond must be supervised by a competent and experienced geo-technical professional.</p> <p>(i) The liner must be certified in accordance with section 17 (Liner certification) of Water Quality Protection Note 27 – Liners for containing pollutants, using engineered soils (August 2013).</p>

Infrastructure Requirements Table	
Column 1	Column 2
Infrastructure	Requirements (design and construction)
Groundwater monitoring bores	<ul style="list-style-type: none"> <li>(a) New monitoring bores must be installed prior to the commencement of works and maintained until the completion of works.</li> <li>(b) Three new groundwater monitoring bores must be installed which meet the requirements of <i>Minimum Construction Requirements for Water Bores in Australia</i> (AIH 2012).</li> <li>(c) New groundwater monitoring bores must be sited in accordance with the Department of Water <i>Water Quality Protection Note 30 Groundwater Monitoring Bores</i> (DoW 2009).</li> <li>(d) New groundwater monitoring bores must be sited with the Chief Executive Officer's (CEO) approval: <ul style="list-style-type: none"> <li>(i) one up-gradient of the infrastructure; and</li> <li>(ii) two down-gradient of the infrastructure;</li> </ul> </li> <li>(e) New groundwater monitoring bores must be surveyed to allow the ground level (to Australian Height Datum) at each location be accurately determined.</li> </ul>

## Records and Information

9. The Works Approval Holder must maintain accurate records including information, reports and data in relation to the Works.
10. All information and records required under this Works Approval must:
  - (a) be legible;
  - (b) if amended, be amended in such a ways that the original and subsequent amendments remain legible or are capable of retrieval; and
  - (c) be retained for six years after the expiry of this Works Approval

## Reports

11. If requested by the CEO from time to time, the Works Approval Holder must provide the CEO with reports or information relating to the Works, the Premises or any condition in this Works Approval (including data from any monitoring conditions, environmental risk assessment studies).
12. Reports or information must be in such form as the CEO may require in a CEO Request.

## Requests for Information

13. The Works Approval Holder must comply with a CEO Request within seven days from the date of the CEO Request or such other period specified in the CEO Request.

## Definitions and Interpretation

### Definitions

In this Works Approval, the following terms have the following meanings:

**CEO Request** means a request made by the CEO to the Works Approval Holder in writing, sent to the Works Approval Holder's address for notifications as described at the front of this Works Approval, in relation to:

- (a) information, records or reports in relation to specific matters in connection with this Works Approval including in relation to compliance with any conditions and the calculation of fees (whether or not a breach of condition or the EP Act is suspected); or
- (b) reporting, records or administrative matters:
  - (i) which apply to all works approvals granted under the EP Act; or
  - (ii) which apply to specified categories of works approvals within which this Works Approval falls.

**Condition** means a condition to which this Works Approval is subject under s 62 of the EP Act, and as set out in section 2 of this Works Approval.

**Premises** refers to the premises to which this Works Approval applies, as specified at the front of this Works Approval and as shown on the map in Schedule 1 to this Works Approval.

**Works Approval** refers to this document, which evidences the grant of the works approval by the CEO under s 57 of the EP Act, subject to the conditions.

**Works Approval Holder** refers to the occupier of the premises being the person to whom this Works Approval has been granted, as specified at the front of this Works Approval.

### Interpretation

In this Works Approval:

- (a) the words "including", "includes" and "include" will be read as if followed by the words "without limitation";
- (b) where any word or phrase is given a defined meaning, any other part of speech or other grammatical form of that word or phrase has a corresponding meaning;
- (c) where tables are used in a Condition, each row in a table constitutes a separate Condition; and
- (d) any reference to an Australian or other standard, guideline or code of practice in this Works Approval means the version of the standard, guideline or code of practice in force at the time of granting of this Works Approval and includes any amendments to the standard, guideline or code of practice which may occur from time to time during the course of the Works Approval.

## Works Approval document history

Where this Works Approval has been amended and revised Works Approvals have been issued, the document history is set out below.


Amendment Description	Date	Revision No
First issue	28 September 2015	0



## Schedule 1: Maps

### 1. Premises Map

The Premises are shown in the map below. The pink line depicts the boundary to the Premises.





## Schedule 2: Works

The Works to be carried out on the Premises are specified in the table below:

Item	Works	Specifications/Drawings
1	Nine Finisher Sheds	<p>9 standard colorbond Surfmist buildings each 13.0 m wide and 101.5 m long (measured inside) placed North-South and connected with a 2.5 m wide passage (18 fully separated sections). Each section contains a total of 36 pens in 2 rows each 6.0 m deep and 2.75 m broad.</p> <p>Plan - Site plan general layout</p> <p>Plan - Layout and Elevations 102m x 13.1m Finisher Shed</p>
2	Waste Treatment Plant	<p>Initial collection tank (feeding tank) – constructed from 316L stainless steel; total capacity 115m<sup>3</sup>; available capacity 96m<sup>3</sup>; shredder; effluent/solids separator.</p> <p>Digester tank - diameter 23m; total height 6m; effective height 5.3m; available volume 2,492m<sup>3</sup>; estimated total time of retention of 25 days; constructed from 316L stainless steel; insulated; elastic gasometrical dome cover; effluent/solids separator.</p> <p>Gas treatment system; 2x200kW gas engines; biogas combustion flare.</p> <p>Plan - Waste Treatment Plant General Layout</p> <p>Plan - Waste Treatment Plant Elevations</p>
3	Evaporation Pond	<p>Depth ex freeboard 1 m (freeboard 0.5 m)</p> <p>Length at crest 360 m; width at crest 100 m</p> <p>Internal Batter 2.5 :1</p> <p>Surface area 36,000 m<sup>2</sup></p> <p>Internal capacity 33,725 m<sup>3</sup></p> <p>Lined with a clay to a permeability less than 1x10<sup>-9</sup>m/s</p> <p>Plan - Pond Layout Plan</p> <p>Plan - Pond Layout – Details</p>
4	Feed Mill	<p>Equipment will be place inside a shed and on a 200mm thick concrete floor:</p> <ul style="list-style-type: none"> <li>• weighbridge and grain intake placed adjacent to shed;</li> <li>• 1,400 tonne of grain and meal storage silos placed adjacent to shed;</li> <li>• a 10 tonne per hour grinder placed inside the shed;</li> <li>• minerals and vitamins dosing system placed inside the shed;</li> <li>• a mixer placed inside the shed;</li> <li>• 297 tonne ready-made feed silos placed adjacent to shed; and</li> <li>• a control room</li> </ul> <p>Plan - 10Tp/h Mash mill Layout</p>
5	Stormwater Pond	<p>Depth ex freeboard 2.5m (freeboard 0.5m)</p> <p>Length at crest 8 m</p> <p>Width at crest 80m</p> <p>Internal Batter 2.5 :1</p> <p>Surface area 6,400 m<sup>2</sup></p> <p>Internal capacity 13,598 m<sup>3</sup></p>


### **Schedule 3: Site Plans**

---


The Site Plans are shown in the following plans.

1. Site plan general layout
2. Layout and Elevations 102m x 13.1m Finisher Shed
3. Waste Treatment Plant General Layout
4. Waste Treatment Plant Elevations
5. Pond Layout Plan
6. Pond Layout – Details
7. 10Tp/h Mash Mill Layout






LAYOUT




SIDEWALL ELEVATION



ENDWALL ELEVATION

# STOCKING DETAILS

PEN SIZE	6000mmL x 2750mmW x 1000mmH
NO. OF PENS	72 per Shed
PEN PER SHED	144
AREA PER PEN	16.41m <sup>2</sup>
ENTRANCE HEIGHT	0.75m
EXIT HEIGHT	300mm
FEDDER	1600mm
CONCRETE SLATS	450 x 800 Liquid Feed Trough every 2nd divider
	6 rows - 1600 x 400 x 70 Green Slats
	2 rows - 1700 x 400 x 70 Green Slats



CROSS SECTION

## GD PORK

### LAYOUT AND ELEVATIONS

102m x 13.1m FINISHER SHED


NOT TO SCALE

A4


DIMENSIONS IN MILLIMETER









LAYOUT



SIDEWALL ELEVATION



ENDWALL ELEVATION



STOCKING DETAILS

PEN SIZE	6000mmL x 2750mmW x 1000mmH
No. OF PENS	72 per Shed
PCS PER SHED	1440
AREA PER PG	0.75m²
ENTRANCE WEIGHT	20Kgs
EXIT WEIGHT	100Kgs
FEDDER	450 x 600 Liquid Feed Trough every 2nd divider
CONCRETE SLATS	6 rows - 1500 x 400 x 70 Green Slats
	2 rows - 1700 x 400 x 70 Green Slats

GD PORK

LAYOUT AND ELEVATIONS


102m x 13.1m FINISHER SHED 1-6

NOT TO SCALE

A4

DIMENSIONS IN MILLIMETER





1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
84



**THE GREEN CONNECTION**

With the Green Connection, you can help protect the environment while growing your business.

PRODUCTION OF ELECTRICITY AND HEAT  
FROM BIOMASS AND ANIMAL MANURE  
INSTALLED POWER: 330 kW

STOMACH	GD PORK
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

1/1	GENERAL LAYOUT
-----	----------------

PRELIMINARY DESIGN

AND FURTHER IN DESIGN OF PROJECT FACILITIES AND REQUIRE THE DESIGN OF FACILITIES OF ALL OF TECHNICAL DESIGN AND  
 PROJECT FACILITIES  
 Required by a  
 AND THESE GUIDELINES MUST BE INCORPORATED IN THE DESIGN  
 THE CHARGE TO DESIGN A PARTIAL OF THE PROJECT FACILITIES  
 THE CHARGE TO DESIGN A PARTIAL OF THE PROJECT FACILITIES  
 THE CHARGE TO DESIGN A PARTIAL OF THE PROJECT FACILITIES

[illegible]





**TRILogy**  
 (800) 440-7440  
[www.trilogy.com](http://www.trilogy.com)  
 300 West 10th Street, Suite 1000  
 Omaha, NE 68102

## WTP PLANT

PRODUCTION OF ELECTRICITY AND HEAT  
FROM ANIMAL SEWAGE & MANURE  
INSTALLED POWER: 380 kW

CUSTOMER:	GD PORK
-----------	---------

SITE:

1/1	GENERAL VIEWS
-----	---------------

PRELIMINARY DESIGN  
THIS COPY IS ONLY INDICATIVE

TO START FOR THE DESIGN OF PROJECT EXECUTIVE AND MUST RETURN THIS DESIGN FOR ACCEPTANCE FULL OF TECHNICAL SOLUTIONS AND THE PROVISION OF MATERIALS  
Signed by us.

ANY MODIFICATION REQUEST MUST BE SHOWN IN RED ON THIS DESIGN.  
THE FAILURE TO RETURN A TIGHT TURN OF MAIL AT THE COMPANY \_\_\_\_\_  
\_\_\_\_\_ WILL CAUSE OF SUSPENSION DESIGN ON HOLD  
CONFIRMATION BY THE CLIENT

DATE \_\_\_\_\_ SIGNATURE \_\_\_\_\_

[illegible]



## LONGITUDINAL SECTION

SURFACE AREA 36,000 SQ M (2 PONDS)  
DEPTH 1 METRE WITH 500 FREE BOARD



SCALE 1 : 1500

[illegible]

the properties of soft polymeric materials, it is first not relevant, compared with the majority of soft polymers, to the properties of the polymer chains, but rather to the properties of the intermolecular interactions between the polymer chains. The properties of the intermolecular interactions are determined by the chemical structure of the polymer chains, but they are not directly determined by the chemical structure of the polymer chains. The properties of the intermolecular interactions are determined by the chemical structure of the polymer chains, but they are not directly determined by the chemical structure of the polymer chains.



GD PORK  
CRAPELLA ROAD  
KOJONUP


[illegible]



SCALE 1 : 750

[illegible]





Designed by M Lisea	Checked by M Lisea	Approved by - date ML - 2/03/14	Filename Layout.pdf	Date 2/03/14	Scale NTS
This drawing is the property of Skold VMS. Copyright laws apply. 07 55 477 588			10Tph Mash Mill Layout		
SKOLD & VMS			GD Pork Feedmill		Sheet 1/1
			Edition 6		



## Works Approval application under Division 3, Part V *Environmental Protection Act 1986*

**Applicant:** GD Pork Holdings Pty Ltd (ACN 126 978 676)

**Application Number:** W5865/2015/1 (NOS6BJ)

**Premises:** Lot 10 Crapella Road BOSCABEL  
SHIRE OF KOJONUP  
Lot 10 on Plan 23562  
Certificate of Title Volume 2173 Folio 889

**Date of report:** 24 September 2015

### 1. Description of the proposal

The works approval application has been submitted by GD Pork Holdings Pty Ltd (**Applicant**) for the expansion of an existing extensive pig farm situated at Lot 10 Crapella Road, Boscabel, Western Australia. The premises currently operates as a deep litter piggery. The current piggery is not a prescribed premises for the purposes of the *Environment Protection Act 1986* as the pigs are housed in large open covered shelters with a concrete base and straw bedding. These piggeries are not considered intensive as described in categories 2 and 69 of Schedule 1 of the *Environment Protection Regulations 1987*.

The Applicant is seeking approval for the establishment of intensive piggery operations in combination with extensive operations for a total production of 27,360 animals (28,368 Standard Pig Units (SPU)). The expansion of the piggery proposes the use of the existing extensive sheds along with newly constructed infrastructure.

This Decision Report is based on an assessment of the Applicant's Environmental Management Plan dated April 2015 in addition to supplementary information dated 25 June 2015, 30 June 2015 and 11 August 2015 (**Final Application**).

This Decision Report identifies the risks of the Final Application and the proposed controls for these risks. In summary:

- The works approval can be granted subject to conditions reflecting the controls set out in section 6 and conditions for the works approval set out in section 7; and
- Any future licence will contain likely conditions set out in section 8.

## 2. Proposed Works

The Applicant proposes the following works:

- Nine tunnel/curtain ventilated finisher piggery sheds;
- An evaporation pond with two compartments (33,725 m<sup>3</sup>; lined with clay);
- A stormwater detention basin (13,598 m<sup>3</sup>)
- Silos, liquid feed shed facilities, feed mill; and
- Waste treatment plant consisting of a feed tank (96m<sup>3</sup>; stainless steel), enclosed digester (2,492m<sup>3</sup>; insulated stainless steel) and biogas reuse system.

The works are additional to the following existing infrastructure:

- 36 extensive deep litter sheds;
- Feed silos; and
- Two storm water ponds.

## 3. Other Approvals and Consultation

### 3.1 Planning Approvals

An application was lodged with the Shire of Kojonup (Shire) for planning approval for expansion on 2 May 2015. An assessment of the proposal by a Development Assessment Panel in place of the Shire was required due to the application meeting the value threshold for a mandatory assessment. The Southern Joint Development Assessment Panel (SJDAP) considered the application on 10 August 2015 and approved the application on 10 August 2015. The proposal was referred to Council's ordinary meeting on 15 September 2015 for consideration of the proposal against the Shire's Health Local Laws. Council approved the proposal on 15 September 2015.

### 3.2 Consultation

A summary of the comments received by DER is set out in the table below, together with the identification of environmental risks.

Comments received	Environmental Risk
<b>Public Authorities</b>	
<b>Shire of Kojonup (Shire) 14 August 2015</b> <ul style="list-style-type: none"><li>• The planning application was referred to a Development Assessment Panel to complete the determination for the Shire.</li><li>• The Shire has a Health Local Law that requires piggeries to be approved.</li><li>• The proposal is scheduled to be referred to Council's Ordinary meeting on 15 September 2015.</li><li>• The application was referred by the Shire to the Department of Health for comment.</li></ul>	<ul style="list-style-type: none"><li>• Odour and dust impacts on neighbouring properties</li></ul>



## 4. Location and Siting

### 4.1 People

The draft *Guidance Statement: Separation distances* provides:

Category	Description	Emission and minimum distance (m)
2	Intensive piggery (1000 animals or more): Premises on which pigs are fed, watered and housed in pens	Noise 1000 m  Odour S-Factor  Refer to "Level 1 only of the National Environmental Guidelines for Piggeries" (Australian Pork Limited, 2010)
23	Animal feed manufacturing (1,000 tonnes or more per year): Premises (other than premises within category 15 or 16) on which animal food is manufactured or processed	Noise, dust, odour  500 m

#### 4.1.1 Noise

Sensitive Receptor	Distance from Prescribed Premises
Closest residential dwellings	Approximately 2,300 m to the NE and SW

#### 4.1.2 Odour

Factors	Rural Dwelling	Rural Residential	Town
Level 1 'S' Factor recommended minimum distance (m)	1,505 m	1,962 m	3,269 m
Actual Distance (m)	2,300 m	16,000 m	17,000 m
Applicant calculated minimum distance (based on Level 1 'S' Factor) (m)	1,500 m	2,000 m	3,300 m

### 4.2 Sensitive ecosystems

Sensitive ecosystems	Distance from Prescribed Premises
Wetland (Salt Lakes)	Salt lake within premises boundary 300 m from evaporation pond 100 m from stormwater ponds and 250 m from waste treatment plant.  Salt Lake (Fitze's swamp) located directly north (160m) of the premises boundary and a number of lakes/swamps located north and southeast.
Watercourse – minor non-perennial	Located within premises boundary connecting to the swamp 160 m north of the premises boundary, approximately 40 m from new accommodation sheds.  Located east of the premises boundary, connecting to an area subject to inundation that connects to Fitze's swamp.
Blackwood Floodplain	2,700 m
Beaufort River	4,000 m

### 4.3 Groundwater and water sources

Groundwater and water sources	Distance from Prescribed Premises
Groundwater as a resource (beneficial use)	Moderate-major groundwater resource located approximately 80 m north of the premises boundary. The groundwater resource is described as a sedimentary aquifer containing sedimentary rocks with intergranular porosity in palaeochannels.
Bore users* (beneficial use)	Four bores located within 1 km radius of the site boundary identified using WIN groundwater layer. Two bores identified as a Department of Water “project bore: operation” and “project bore: production”, other two identified as “no current owner” or “not operational”  Department of Agriculture desk top assessment has indicated that there is a potable supply bore on the northern boundary of the premises. Salinity from the bore is approximately 2300 mg/L-3000 mg/L
Beaufort River	4,000 m

\*Bore locations identified through WIN Groundwater Sites GIS data.

### 4.4 Other site characteristics

Other characteristic	Distance from Prescribed Premises
Area subject to inundation	Located within premises boundary, in the proposed location of the new stormwater basin

## 5. Inherent risks to amenity, public health or environment

The table below sets out the risks arising from the application. These risks are then assessed taking into account the controls proposed by the Applicant. The regulatory controls corresponding to these risks are set out in section 6.

	Emission source	Emission (type and quantity)	Pathway	Receptor	Proponent Controls	Consequence	Likelihood	Risk Rating
1.	Noise generated through housing of pigs in extensive and intensive shelters	Noise	Emission to air Transmission through air	Rural dwelling 2,300 m	Separation distance  Stress of animals will be minimal as a result of readily available feeding	Insignificant	Unlikely	Low risk of nuisance and disturbance for residents
2.	Odour generated through accommodation sheds and the breakdown of biological material through evaporative ponds and carcass composting facility	Odour	Emission to air Odour emissions move with direction of wind	Rural dwelling 2,300 m	Separation distance  Cover and ventilation of sheds  Cleaning regime	Insignificant	Unlikely	Low risk of odour affecting public amenity
3.	Nutrient rich slurry and waters from sheds	Slurry and wastewater (31,505 tpa), and deep litter (2,924 tpa) containing elevated levels of nutrients	Emission to land or waters  Leakage and seepage direct into ground or into surrounding watercourses	Minor non-perennial watercourse 40 m from the intensive sheds.  Onsite geomorphic wetland approximately 300 m from the sheds  In situ soils	Separation distance  Plug and pull effluent collection system and covered concrete collection sump  Concrete floor sheds  Spent deep litter removed to WTP	Moderate	Unlikely	Moderate risk of eutrophication of receiving surface water bodies

	Emission source	Emission (type and quantity)	Pathway	Receptor	Proponent Controls	Consequence	Likelihood	Risk Rating
4.	Stormwater and leachate from storage of waste materials (spent litter, carcasses, slurry and pressed digestate manure)	Nutrient-rich stormwater and leachate (nutrient concentrations of manure, slurry and carcasses contained in Appendix 2 of the EMP)	Emission to land or waters  Contaminated stormwater and leachate running directly from the waste material	Minor non-perennial watercourse approximately 150 m from the storage areas  Onsite geomorphic wetland 250 m from the waste storage areas at the WTP  In situ soils	Separation distance  Covered concrete slurry collection sump  Bunded concrete spent litter storage area with a capacity of 300m <sup>3</sup>  Waste treatment plant consisting of impervious: <ul style="list-style-type: none"> <li>• 96 m<sup>3</sup> feeding tank; and</li> <li>• Enclosed 2,492 m<sup>3</sup> digester</li> </ul> Bunded concrete pressed manure storage area with separation station return to WTP feeding tank  Collection and diversion of clean stormwater to stormwater dam	Moderate	Unlikely	Moderate risk of eutrophication of receiving surface water bodies
5.	Biogas capture and discharge through the anaerobic digestion	Biogas is a mixture of gases consisting of methane, carbon dioxide, hydrogen sulfide and traces of ammonia, hydrogen, nitrogen and carbon monoxide	Emission to air  Odorous emissions move with direction of wind	Rural dwelling 2,300 m	Contemporary engine designed for biogas fuel  Quality of biogas monitored and metered  Regular inspection and maintenance of engines	Insignificant	Unlikely	Low risk of impact to amenity of residents

	Emission source	Emission (type and quantity)	Pathway	Receptor	Proponent Controls	Consequence	Likelihood	Risk Rating
6.	Storage of treated wastewater in evaporation pond	Nutrient-rich treated wastewater potentially containing pathogens (38 tpa nitrogen, 11 tpa phosphorous). Total water input is 70 tpd	<p>Emission to water</p> <p>Seepage of treated wastewater into groundwater from leaks or seepage through the pond base</p> <p>Direction of groundwater flow is unknown</p>	<p>Granitic basement overlain by a thick (up to 30m) weathered profile comprising mainly of materials with a clayey to sandy-clay texture</p> <p>Supporting Environmental Management Plan determines depth to permanent groundwater indicated as between 5-10 m below ground level (mBGL). Depth to shallow perched groundwater indicated to be approximately 2 m BGL</p> <p>Four bores located within 1 km radius of the site including a potable water bore identified by Department of Food and Agriculture desktop assessment within 680m of the pond</p>	<p>Siting - the separation distance from the base of the wastewater pond to the highest groundwater level is expected to be greater than 2 m</p> <p>Evaporation pond is lined with 300mm of clay engineered to a permeability of less than <math>1 \times 10^{-9}</math> m/s</p> <p>Ambient groundwater monitoring</p> <p>The pond has two compartments to allow inspection of the lining if required</p>	Moderate	Unlikely	Moderate risk of seeping to groundwater

	Emission source	Emission (type and quantity)	Pathway	Receptor	Proponent Controls	Consequence	Likelihood	Risk Rating
7.	Overtopping of treated wastewater entering land and waters	Nutrient-rich treated wastewater potentially containing pathogens (38 tpa nitrogen, 11 tpa phosphorous). Total water input is 70 tpd	Emission to land  Overtopping or breach of treated liquid waste from evaporation pond  Direct runoff of treated wastewater or infiltration into ground	Onsite geomorphic wetland 300 m from the pond  In situ soils	Separation distance - establishing minimum separation distance of 50 m between wetlands and wastewater pond.  Pond sized based on water balance calculation and number of pigs to ensure sufficient capacity  500 mm freeboard  The pond has two compartments to allow desludging to occur  Separation of clean stormwater to stormwater dams	Moderate	Possible	Moderate risk of causing eutrophication of receiving surface water bodies



## 6. Regulatory Controls

This section sets out regulatory controls. The controls correlate to the risks identified in section 5 as set out in the table below.

			Controls (see sections below)				
			6.1 Siting controls	6.2 Ambient monitoring	6.3.1 Shed and waste handling infrastructure	6.3.2 Waste treatment plant infrastructure	6.3.3 Evaporation pond infrastructure
Risk Items (see section 5)	1	Noise from generated through housing of pigs impacting public amenity	Low risk. No control required.				
	2	Odour generated through housing of pigs impacting public amenity	Low risk. No control required.				
	3	Leakage of nutrient rich slurry and waters from sheds entering land and waters causing eutrophication of receiving surface water bodies	•	•	•		
	4	Stormwater and leachate from storage of waste materials entering land and waters causing eutrophication of receiving surface water bodies	•	•	•	•	•
	5	Biogas impacting public amenity	Low risk. No control required.				
	6	Storage of treated wastewater in evaporation pond seeping to groundwater.	•	•			•
	7	Overtopping of treated wastewater	•	•			•

Controls comprise of:

- key elements of the infrastructure as set out in the Final Application; and
- the Chief Executive Officer's (CEO) requirements which are necessary and convenient to ensure that the activities pose an acceptable level of risk to public health and the environment.

CEO requirements have been identified at the end of each specification.

### 6.1 Siting controls

#### 6.1.1 Groundwater

- The evaporation pond must have a minimum 2m separation to groundwater.
- Exact distances to groundwater must be certified prior to commencement of construction.

Separation to groundwater refers to the vertical separation of the infrastructure calculated from the underside of the lowest point to the highest point of the highest seasonal water table.

### **6.1.2 Wetlands**

The evaporation pond and piggery infrastructure (with the exception of stormwater dams) must be located at least 50m from geomorphic wetlands.

The distance from infrastructure must be calculated from the outer perimeter of any embankment or physical building.

## **6.2 Ambient groundwater monitoring**

- (a) New monitoring bores must be installed prior to the commencement of works and maintained until the completion of works.
- (b) Three new groundwater monitoring bores must be installed which meet the requirements of *Minimum Construction Requirements for Water Bores in Australia* (AIH 2012).
- (c) New groundwater monitoring bores must be sited in accordance with the Department of Water *Water Quality Protection Note 30 Groundwater Monitoring Bores* (DoW 2009).
- (d) New groundwater monitoring bores must be sited with the Chief Executive Officer's (CEO) approval:
  - (i) one up-gradient of the infrastructure; and
  - (ii) two down-gradient of the infrastructure;
- (e) New groundwater monitoring bores must be surveyed to allow the ground level (to Australian Height Datum) at each location be accurately determined.

## **6.3 Infrastructure specifications**

### **6.3.1 Sheds and Waste Handling System**

The wastewater treatment system must be designed and constructed so as to meet the following specifications:

- (a) Finisher sheds must comprise slatted concrete floors and contain continuous feeding system to all animals within the shed.
- (b) Employ pull and plug systems for all finisher sheds, as described in the Environment Management Plan, comprising of impermeable, corrosion resistant and sturdy underfloor pits and covered concrete collection sump.
- (c) Ensure all wastewater and slurry from the intensive piggery sheds is directed to the wastewater treatment plant by 300mm diameter impermeable PVC piping.
- (d) Ensure all waste storage and treatment areas are constructed from impermeable concrete hardstand.

### **6.3.2 Waste Treatment Plant**

Following construction and commissioning of the Waste Treatment Plant certification must be provided from a suitably qualified professional that:

- (a) the plant has no major operational defects; and
- (b) is fit for the purpose intended being the treatment of waste from the maximum number of SPUs to be held on the premises.

### **6.3.3 Evaporation Pond**

- (a) The evaporation pond to be constructed in accordance with the documentation provided through the application and supporting documentation and to meet the following specifications:

- (i) minimum internal capacity of 33,725 m<sup>3</sup>;
  - (ii) minimum surface area of 36,000 m<sup>2</sup>;
  - (iii) minimum length at crest of 360 m;
  - (iv) minimum width at crest of 100 m;
  - (v) internal batter not exceeding 1:2.5 (horizontal:vertical); and
  - (vi) maximum water depth of 1m (not including freeboard).
- (b) Soils used for the lining of the evaporation pond must be free from plant roots and reactive, soluble and organic matter.
- (c) The liner material used for the evaporation pond must meet the following criteria:
- (i) percentage fines with acceptability of:
    - (a) more than 25 per cent passing a 75 micron sieve; and
    - (b) more than 15 per cent passing a 2 micron sieve, tested using AS 1289 3.6.1-2009
  - (ii) liquid limit with acceptability of 30 to 70 per cent tested using AS 1289 3.1.2-2009.
  - (iii) plasticity index with acceptability of more than 15, tested using method AS 1289 3.3.1-2009.
  - (iv) Emerson class number with acceptability of 5 to 6 tested using AS 1289 3.8.1-2006.
- (d) The liner material must be homogeneous in nature and properties, with no sandy patches exceeding the liner specification or rocks retained on a 37.5 mm sieve.
- (e) The liner must be installed in at least two layers of equal thickness to ensure adequate compaction is achieved and be moisture-conditioned to achieve the maximum design soil density exceeding the 95 per cent maximum (in place) dry density (MDD) determined using AS 1289.5.2.1 (2003) and AS 1289 5.4.1 (2007).
- (f) The minimum thickness of the compacted soil liner should be 300 mm with a tolerance of 5 mm.
- (g) The compacted liner must uniformly cover both the base and perimeter of the pond to achieve one integrated holding pond.
- (h) The construction of the lined pond must be supervised by a competent and experienced geo-technical professional.
- (i) The liner must be certified in accordance with section 17 (Liner certification) of Water Quality Protection Note 27 – Liners for containing pollutants, using engineered soils (August 2013).

## 7 Conditions for the works approval

Controls will be conditioned in the works approval instrument by:

- a condition specifying that prior to commencement of the works, the Applicant will be required to provide the CEO with engineered certification that the drawings and systems comply with the relevant controls; and
- a condition specifying that on completion of the works, the Applicant will be required to provide the CEO with engineered certification that the as built works comply with the relevant controls.

## 8 Conditions for the licence

Any future licence may include conditions regarding management of stormwater, waste storage, the waste treatment plant, and the evaporation pond (including maintaining a freeboard of 500 mm). Conditions for maintenance of containment infrastructure, seepage assessment, groundwater monitoring, specified animal numbers and reporting requirements may be included on the licence.

The works include a feedmill which will have the capacity to produce 10 tonne of feed per hour. The feedmill is within Category 23 “Animal feed manufacturing” of Schedule 1 to the *Environmental Protection Regulations 1987*. The main environmental risk of the feedmill is noise and dust, which may be subject to conditions on the licence.

## 9 Conclusion

Based on the assessment of the Final Application and the environmental impacts that may result from the proposal to expand the piggery, it has been determined that a Works Approval will be granted that is subject to the regulatory controls and conditions outlined in this decision report to mitigate the identified environmental risks.

**Kelly Faulkner**

**Executive Director Licensing and Approvals**

delegated Officer under section 20 of the *Environmental Protection Act 1986*