Application form annex: Category checklist (solid waste landfill sites)

Part V Division 3, *Environmental Protection Act 1986*Environmental Protection Regulations 1987

INSTRUCTIONS:

- This checklist outlines additional information requirements for applications under Part V Division 3 of the Environmental Protection Act 1986 (EP Act) to:
 - construct and operate new solid waste landfills, or
 - amend an instrument granted for an existing landfill (i.e. new cells/landfill areas at an existing landfill facility).
- This checklist must be completed and submitted as an attachment to the main 'works approval, licence
 or amendment application form' (see Part 12 of that form). Notes included throughout this checklist
 must be read in conjunction with the instructions and requirements of the main application form.
- The application checklist must be completed with all relevant information attached. Information
 requirements and attachments can be combined and submitted as one or more consolidated documents
 if desired, provided it is clear to which section of the application checklist the information/attachments
 relate.
- If an application form and checklist has been submitted and are incomplete the Chief Executive Officer (CEO) of the Department of Water and Environmental Regulation (DWER) will decline or return the application (as applicable).
- The information requirements outlined in this checklist are not exhaustive. Applicants are advised to
 provide additional supporting information and environmental investigations as required to support the
 application and assessment process.
- This checklist does not apply to landfill sites that are associated with mining operations or for rural landfill premises (premises specified in Schedule 1 Part 2 of the Environmental Protection Regulations 1987 as category 89 premises).
 - However, depending on the environmental context of the proposed landfill site, DWER may still require applicants to provide a similar level of detail to support their application. Mine site and rural landfill operators should consider the environmental siting of the proposed landfill site and, depending on the site sensitivity, should contact DWER to seek advice on the likely specific information requirements, prior to submitting an application.

Completion matrix

The matrix below explains what sections are required to be completed for different types of landfill applications. The class and category of landfill is outlined in Schedule 1 of the Environmental Protection Regulations 1987.

	Prescribed premises category and landfill class					
Form section	Category 63	Category 64	Category 64	Category 65	Category 66	
	Class I	Class II	Class III	Class IV	Class V	
Part 1: Environmental siting and Conceptual Site Model	•	•	•	•	•	
Part 2: Landfill design and construction	•	•	•	•	•	
Part 2A: Design and construction overview	•	•	•	•	•	
Part 2B: Landfill liner specifications	N/A	•	•	•	•	
Part 2C: Stability assessment	N/A	•	•	•	•	
Part 2D: Leachate management	N/A	•	•	•	•	
Part 2E: Landfill gas management	N/A	•	•	•	•	
Part 2F: Stormwater/surface water management	•	•	•	•	•	
Part 2G: Monitoring requirements	•	•	•	•	•	
Part 3: Premises operations	•	•	•	•	•	
Part 4: Landfill closure and rehabilitation	•	•	•	•	•	

Key:

Must be submitted

N/A Not required with application, or not applicable in the context of the scope of works and operations.

Part 1: Environmental siting and conceptual site model (CSM)

INSTRUCTIONS:

- Refer to DWER's <u>Guideline: Environmental siting</u> for details of the specified ecosystems and other environmental attributes considered in DWER's assessment.
- The supporting information provided as part of an application must provide sufficient evidence to allow DWER to make a reasonable decision.

	allow DWER to make a reasonable decision.	
		Yes
1.1	Siting context and background	\boxtimes
	Provide a description of:	
	history of the site (past and current activities)	
	land ownership	
	the local area and the landfill's siting within this area	
	surrounding land uses	
	community and/or stakeholder need for landfill site.	
	Refer to Section 2 of the Environmental Assessment and Management Plan	
1.2	Sensitive receptors and designated areas (within a 2 km radius¹)	\boxtimes
	Provide information on the distance and directions to sensitive environmental and human receptors including:	
	• human receptors (e.g. residential, rural, industrial / commercial, and/or recreational premises)	
	surface waters (permanent and seasonal)	
	depth to groundwater and potential beneficial use(s)	
	sensitive flora and fauna	
	designated areas ²	
	regional and local catchment characteristics.	
	And other sensitive receptors as identified in the Guideline: Environmental siting.	
	Note 1: depending on the proposed landfill class and site context, a larger radius may need to be assessed.	
	Note 2: designated areas as defined by section 57 of the EP Act and comprise water source areas proclaimed under the <i>Rights in Water and Irrigation Act 1914</i> , and Public Drinking Water Source Areas proclaimed under the <i>Country Areas Water Supply Act 1947</i> and <i>Metropolitan Water Supply, Sewerage, and Drainage Act 1909</i> .	
	Refer to Section 2 and 3 of the Environmental Assessment and Management Plan	
1.3	Local climate and meteorological data	\boxtimes
	Provide information on the local climate and meteorological data, including:	
	monthly rainfall	
	monthly evaporation	
	wind conditions (seasonal wind strength and direction)	
	 source and date range of meteorological data (e.g. on-site weather station or from a Bureau of Meteorology [BoM] site; site details must be provided). 	
	Refer to Section 3 of the Environmental Assessment and Management Plan	
1.4	Topography, geology and hydrology	\boxtimes
	Provide information on the topography, geology and hydrogeology of the area including:	
	surface elevation and topography	
	 regional and local geology³ and soils³ including site-specific soil and geological records where available 	
	regional and local hydrology	
	groundwater flow direction and rate ³	
	groundwater quality ³ and current or future use	
	groundwater aquifer characteristics	
	a description of geologic active processes (e.g. faulting, subsidence) (if applicable).	
	Note 3: site-specific investigations should be undertaken where information on local attributes is not available in published documentation or digital datasets. Whether relying on published information or the results of site investigations, applicants must provide references and demonstrate that the information presented is representative of site conditions.	
	Refer to Section 3 of the Environmental Assessment and Management Plan	

Part 1: Environmental siting and conceptual site model (CSM) 1.5 Conceptual site model

 \boxtimes

Provide a site-specific conceptual site model (CSM)⁴ which clearly identifies all potential source-pathway-receptor (S-P-R) linkages for all related environmental media (Section 1.8 below – Attachment 3).

The development of the CSM is an iterative process, whereby the initial CSM is developed in the first stage of conceptual design/assessment (taking into consideration the nature of baseline environmental conditions) and revised as more detailed information on the site and the nature of potential risk events becomes available. The CSM is also used to identify uncertainties or critical gaps in information that may need to be addressed through additional investigations.

The complexity of the CSM corresponds to the scale and complexity of the landfill activities and should be devised to help in the design process to identify appropriate design and operational measures as well as environmental monitoring requirements.

Note 4: guidance on developing CSM's can be sourced in DWER's <u>Assessment and management of contaminated sites guidelines</u> and from Schedule B2 of the <u>National Environment Protection (Assessment of Site Contamination) Measure 1999</u> (NEPM).

Refer to Section 7, 8 and 9 of the Environmental Assessment and Management Plan.

Attach	ments		N/A	Yes
1.6	Attachment 1: Locality map(s)	An aerial photograph, map, and/or site plan of sufficient scale showing the proposed prescribed premises boundary and general locality of the premises in respect to nearby sensitive receptors and surrounding land uses. Multiple maps at different scales can be provided.		
1.7	Attachment 2: Topography, geology and hydrogeological plans/maps	An aerial overview and cross-section drawings of topographical, geological, and hydrogeological features related to the site.		\boxtimes
1.8	Attachment 3: Conceptual site model	In accordance with Part 1.5 above, provide a CSM in table format. A graphical representation can also be developed and submitted to help illustrate S-P-R linkages. An example table format is provided below. Refer to Section 9.5 where the Residual Risk Profile has been summarised in table format.		\boxtimes

Example CSM table:

Source / activities	Pollutant or contaminant of potential concern	Pathway (transport mechanism)	Receptor	Potential impacts
Leachate Pond 1	Metals, TDS, nutrients, BOD, organic acids, petroleum hydrocarbons, sulfides, alkanes, PFAS	Infiltration; vertical migration to the subsurface and groundwater. Horizontal migration in groundwater along the downgradient flow path. Abstraction of groundwater for nonpotable uses (garden irrigation and other nonpotable uses).	Underlying groundwater (15mBGL). Down-hydraulic gradient non-potable groundwater users – 8 licensed bores identified, unlicensed domestic bores may also be present (400m southwest). Conservation category wetland located downhydraulic gradient (300m south-west) – considered a 'flow-through wetland' which is in direct hydraulic connection with the watertable aquifer.	Groundwater degradation and impacts to downgradient groundwater users. Impacts to wetland water quality and ecosystem disturbance.
Landfill	Landfill gas	Subsurface lateral migration along preferential pathways.	On-site office administration accommodation 150m from the proposal landfill cell.	Accumulation of LFG in subsurface structures and conduits presenting a potential explosion hazard.

Part 2: Landfill design and construction

INSTRUCTIONS:

- This section is made up of 7 sub-parts focusing on landfill design and construction:
 - Part 2A: Design overview and construction scope
 - Part 2B: Landfill liner specifications
 - Part 2C: Stability assessment
 - Part 2D: Leachate management
 - Part 2E: Landfill gas management
 - Part 2F: Stormwater/surface water management
 - Part 2G: Monitoring requirements
- The proposed design should consider and acknowledge the interactions between these elements and take into consideration the environment setting, adjacent current and future land uses, available materials and infrastructure, waste to be received and the need to provide integrated waste management facilities (disposal and recycling options).
- The CSM (required under Part 1.5) will help operators in gaining an understanding of the environmental setting and potential risk events and should be considered in the design and operation of the landfill.
- Where an application is for a category 63 (Class I landfill), but not any other landfill category, only subparts 2A, 2F, and 2G must be completed; Parts 2B to 2E are either optional or not applicable.

Part 2A: Design overview and construction works

INSTRUCTIONS:

- This section requires applicants to provide an overview of the proposed landfill design concept including all related infrastructure, such as leachate and landfill gas management infrastructure.
- This section also requires a detailed summary of the extent of construction works that are being proposed under this application to clarify the scope of assessment.

		Yes
2.1	Landfill design concept	\boxtimes
	Provide information on each component of the proposed landfill including (but not limited to):	
	 landfill type and design concept: including details on size (spatial and volumetric), lifespan, geometry, proposed liner⁵ and leachate management system⁵ and groundwater and surface water management⁵ (specified design detail must be provided for each proposed landfill cell) 	
	waste types proposed for disposal ⁶	
	 details on the landfill cell(s) that will be subject of this application and staging of development 	
	 site infrastructure layout including details on traffic access and internal haul routes, and details on all facilities for receiving and handling waste and administration of the landfill. 	
	Note 5: Only an overview of this information is required under this part. Specific information requirements for each of these aspects is outlined further in subsequent parts of the application checklist.	
	Note 6: Information must be consistent with the requirements outlined in Part 9.2 of the main works approval or licence application form (waste-related activities).	
	Refer to Section 5 of the Environmental Assessment and Management Plan	
2.2	Scope of construction works	\boxtimes
	Provide details of construction works including:	
	general site preparation works ^{7,8}	
	infrastructure to be constructed	
	construction phases and associated timings of works	
	 construction quality assurance (CQA) measures and procedures to be employed⁹ 	
	 summary of management measures and controls to be adopted for noise, dust and odour emissions (odour in the case where new cells are tying in with existing cells) and for the management of stormwater, general erosion and sediment control¹⁰ 	
	Note 7: Certain site preparation works may be undertaken without a works approval. Refer to Section 3 of the <i>Guideline: Industry Regulation Guide to Licensing</i> for further information.	
	Note 8: Provide a general overview of site preparation works. Specific preparatory works in relation to the landfill liner, leachate pond and landfill cap are detailed respectively in Part 2B, Part 2E, and Part 4.	

Part 2A: Design overview and construction works Note 9: Part 2B of this checklist outlines specific CQA information requirements for the liner installation. It is

essential that you adopt a quality approach to landfill engineering. CQA techniques help in providing confidence that construction works have been completed in accordance with the design specifications and, where non-conformances are identified, that appropriate corrective actions are taken. Typically for landfill applications, applicants should provide a CQA plan prepared in conjunction with design engineers and relevant CQA specialists.

Note 10: Information must be consistent with the requirements outlined in Part 9.1 of the main works approval or licence application form (potential emissions and discharges arising from the proposed activities).

Refer to Section 5 of the Environmental Assessment and Management Plan as well as Appendix B and Appendix C for the Technical Specifications and CQA Plans developed for Cells 7.

2.3 Attachment 4: **Premises** map and site layout plan(s)

Attachments

A premises map and site layout plan must be provided, which include the following:

- premises boundary
- site layout depicting all infrastructure (current and proposed)
- location of the works (cells, leachate ponds, etc.) and any potential future cells/ponds (as applicable)
- stormwater infrastructure
- access and haulage roads
- other key buildings (gatehouse, weighbridge, administration office, etc.)
- scale and north arrow; GPS coordinates and legend.

Refer to Figure 4 and the Drawing set in Appendix A of the Environmental Assessment and Management Plan.

2.5 Attachment 5: Detailed design drawings (multiple as required)

Detailed design drawings:11

- cell layout
- landfill geometry
- schematic cross sections of the landfill cell(s)
- leachate pond layout and cross sections
- landfill cap.

Note 11: Additional design drawings are required for the proposed liner, leachate management system and landfill cap as detailed respectively in Part 2B, Part 2E, and

Refer to Figure 4 and the Drawing set in Appendix A of the Environmental Assessment and Management Plan.

Part 2B: Landfill liner specifications

NOTE:

- The principal functions of a landfill liner system are to limit contaminant migration to groundwater and to control landfill gas migration.
- Construction quality assurance (CQA) measures must be in place to ensure construction of the engineered systems will meet the intended (and assessed) standards and specifications and to provide an audit trail.

		N/A	Yes
2.6	Provide details of the proposed landfill liner system and configuration. A statement of the intended landfill liner performance (overall permeability and containment features) should also be provided in support of the proposed liner system. Components ¹² of the basal and side slope liner may include: Subgrade ¹³ Clay ¹⁴ or geosynthetic clay liner (GCL) High Density Polyethylene (HDPE) geomembrane leachate drainage layer ^{15,16} cushion geotextile layer.		

Yes

X

X

Part 2B	Landfill liner specifications	
	Provide detailed design drawings of the liner system (see Section 2.9 – Attachment 6).	
	Note 12: Thickness, material properties and manufacturer design specifications (including design hydraulic conductivity/permeability) must be provided for each liner component.	
	Note 13: Where the in-situ subgrade is not suitable to form part of the foundation and liner, then an appropriate sub-grade must be constructed.	
	Note 14: Where a natural geological barrier is in place (and forms part of the liner system) you must demonstrate that the barrier extends along the base and all the way up the sides of the landfill site. Details of the in-situ thickness, material properties and any artificial enhancements must be provided. Note 15: Part 2D of this checklist outlines specific information requirements for leachate	
	management (which complement the detail requested in this section).	
	Note 16: Operators may consider the need for a secondary leachate collection system (leak detection layer) to detect any malfunction of the upper primary liner components.	
	Refer to Section 5 of the Environmental Assessment and Management Plan as well as Appendix B and Appendix C for the Technical Specifications and CQA Plans developed for Cells 5 and 6	
2.7	Liner construction and/or installation:	\boxtimes
	Provide information of the proposed construction and/or installation of the liner system. Information should be provided for each individual liner component (as the case requires). Considerations include, but are not limited to:	
	 any preparatory works required, e.g. earthworks/subgrade preparation, compaction methods 	
	handling and storage of liner materials	
	 method of placement (for clay liners include details of thickness and number of lifts, compaction method and required level of compaction) 	
	 keying into existing surfaces (anchor points) and/or tying into adjacent landfill cells 	
	conditions of underlying surface between layers	
	method of jointing for liner installation (e.g. bonding, welding, or seaming)	
	 quality assurance testing (see Section 2.8 below). 	
	Refer to Section 5 of the Environmental Assessment and Management Plan as well as Appendix B and Appendix C for the Technical Specifications and CQA Plans developed for Cells 5 and 6	
2.8	Construction Quality Assurance plan	\boxtimes
	The application should include a Construction Quality Assurance (CQA) plan which includes the proposed testing, inspection, and verification procedures to demonstrate that materials and constructed features at the landfill meet the designs and specifications.	
	The CQA plan should include as a minimum:	
	 descriptions of responsibilities, qualifications and obligations for each party involved in the CQA plan and the proposed level of supervision for liner construction/ installation 	
	 materials testing information, including sampling locations, frequency of testing, test methods, laboratories, accreditations, applicable specifications and quality standards, data evaluation, acceptance and rejection criteria, and contingency measures in the event of failure 	
	 hold and inspection points – these points are typically the start and finish of key stages of the work that cannot later be rectified because they will no longer be accessible 	
	 for geosynthetic materials (i.e. geomembranes, geosynthetic clay liners, geotextiles, geonet drainage geocomposites, and geogrids), the CQA plan should address the following requirements: 	
	 manufacturing quality control – including factory test results, certifications and material warranties 	
	 independent conformance testing – there should be a program of CQA independent conformance testing to verify that the materials supplied comply with the required specifications 	

Part 2B	: Landfill liner spec	cification	s		
	dam orier instri prote	age during tation in a uctions ar ection fron d record l	ocedures – storage to protect from weather and other g installation, panel overlaps, welds, jointing and seam accordance with good practice and the manufacturer's and regular inspections, repairs tested and recorded and n UV light after installation etc.		
	Critical Containment environmental contro are deposited in the	Infrastruct ols on conta containme	undfill construction works, DWER will require operators to submit a ure Report (CCIR). The purpose of the CCIR is to confirm that the ainment infrastructure are properly constructed before materials nt cell (the CCIR is the equivalent of a CQA validation report quired for verification and audit purposes).		
			vironmental Assessment and Management Plan as well as an developed for Cells 5 and 6		
Attachn	nents			N/A	Yes
2.9	Attachment 6:	Provide	detailed design drawings which clearly depict the following:		
	Detailed design drawings –	a)	basal and side wall liner detail (typical section)		\boxtimes
	landfill liner	b)	leachate sump liner detail (typical section)	\boxtimes	
		c)	inferred groundwater levels (mAHD) relative to the base of the landfill cell (mAHD); depicted on cross-section drawings (showing at least two perpendicular planes on the horizontal, e.g. north-south, east-west, or otherwise as appropriate) showing perimeter side slopes/walls. All heights of the base, sump, liner, and the perimeter side walls should be shown in mAHD.		\boxtimes
			Cross sections must clearly demonstrate the separation distance between the lowest point of the landfill cell or leachate sump (whichever is lowest) and the underlying water table.		
		d)	leachate collection system, depicting the distribution and layout of leachate collection pipes, sumps, leachate extraction/removal pipes with appropriate grades/slopes etc.		\boxtimes
		e)	anchor trench detail		\boxtimes
		f)	liner tie in detail and interface between adjacent cells (if required)		
		Ass not will	er to the Drawing set in Appendix A of the Environmental sessment and Management Plan. An independent sump is proposed for Cell 7. The Cell 7 leachate collection layer connect to the existing Cell 5 leachate collection layer and chate will be extracted from the existing Cell 5 sump.		\boxtimes

Part 2C: Stability assessment

- The geotechnical stability of the lining system, wastes and underlying geological strata (foundation)
 must be assessed.
- The stability assessment should take into account the interactions between the multiple layers present in the lining system and must demonstrate structural/physical stability over the entire lifecycle of the landfill.
- Where DWER has previously assessed stability assessments for existing cells, which were considered
 appropriate, and the proposed new cells comprise a similar design then the applicant can justify a
 lower level of stability analysis to that outlined below. In this case the applicant must provide clear
 justification as to the level of analysis undertaken and give regard to and justify the applicability of
 previous assessments carried out to the new proposed landfill area/cell.

		N/A	Yes
2.10	Stability assessment		\square
	Provide a stability assessment which analyses the following aspects as a minimum:		
	liner interface stability		
	a) assessment of the capping liner system (upper surface and slopes)		

Part 2C: Stability assessment

- b) assessment of the basal liner system interfaces
- waste stability
- embankment slope and foundation stability.

Other information requirements:

The software used and chosen model must be detailed and justified and all assumptions and data inputs must be clearly documented and justified.¹⁸

All adopted factors of safety (FoS) must be clearly documented and justified.

Details of the material properties used in the analysis must be provided. Where material properties are not based on site-specific investigations, ¹⁹ clear justification must be provided to demonstrate that they are appropriate for use in the stability assessment.

The assessment must include the elements with the highest risk of instability (critical surfaces) based on interface properties, geometry, sequence of deposition of the waste and subsurface conditions. Interim construction/filling stages must be analysed if the geometry, loading conditions and materials are of risk. Indicate the location of the sections analysed on an appropriate figure and provide justification for why specific elements have been selected (see Section 2.11 – Attachment 7).

Confirm the design assumptions regarding internal leachate phreatic surfaces and external pore pressures for the stability analysis and model the scenarios that account for a build-up of pore water pressure in the lining system and waste during normal and abnormal operations as well as post-operations. At a minimum, the following three internal leachate scenarios must be addressed:

- no phreatic surface
- elevated phreatic surfaces representing hypothetical 'steady state' condition
- high phreatic surface representing a malfunction of the leachate pumps.

For external pore-pressure scenarios, where relevant, the model should consider both average/expected pore pressure condition and highest inferred groundwater level.

A stability analysis must also be performed for pseudo-static conditions to address the effect of a seismic event. The following scenarios must be assessed:

- operation basis earthquake (OBE)
- maximum design earthquake (MDE)
- maximum credible earthquake (MCE).

Methods for determining return period intervals for each scenario must be clearly documented and justified.

A sensitivity analysis must also be carried out for the basal liner system interface to assess the effect of variability of material properties on the stability analysis outcomes.

Note 18: Raw and model data (including modelling files) is not required to be submitted at the time of application but must be able to be provided, in full, on request, so that the stability analysis can be technically verified if necessary.

Note 19: The characterisation of all materials incorporated into the stability assessment must be appropriately described. Site-specific investigations of material properties is recommended in preference to using other data.

Attachments N/A Yes 2.11 Attachment 7: Analysis drawings and/or figures including, but not limited to: X П Stability cell layout; aerial overview depicting analysed sections assessment cell cross-sections depicting analysed sections (include drawings and analysis results in table on figure) figures (multiple as other figures and drawings as required. required) Refer to Appendix D of the Environmental Assessment and Management Plan

Part 2D: Leachate management

- Operators must provide information on the proposed leachate management system including the need to recover leachate from landfill cells and store in appropriately sized leachate holding and evaporation ponds.
- There must be sufficient leachate disposal capacity to prevent the build-up of leachate and an increase in the risks of water pollution and offensive odours.

	2D: Leachate management	NI/A	V
		N/A	Yes
2.12	Leachate management system Provide a description of the proposed leachate management system ²⁰ and method for managing leachate (e.g. evaporation, treatment, re-circulation). A written summary of all the related infrastructure ²¹ should be provided as well as depicted on an appropriately scaled site layout plan (refer to Section 2.14 – Attachment 8).		\boxtimes
	Please also provide the following assessment and management detail:		
	water balance calculation ^{22,23} to predict the volume of leachate generation over time and to demonstrate that the proposed system has sufficient capacity to manage leachate volumes over the operational life of the landfill		
	leachate management and proposed monitoring plan, including:		
	 maximum head of leachate on the liner surface and leachate sump during operation of the landfill 		
	 in-cell leachate monitoring, including the operational controls and infrastructure to be used to control the leachate head 		
	 leachate extraction/pumping system (including details on flow rate) 		
	 leachate pond management, including details on operational freeboard, mechanical aeration equipment (if required), and pond level alarms 		
	o proposed leachate quality monitoring program (refer also to Part 2G)		
	 contingency plans for leachate management in the event of breakdown of various components. 		
	Note 20: Design information requirements for leachate pond design and construction are outlined in Part 2.13 (below).		
	Note 21: Details of the drainage/collection network infrastructure should include information on sumps, collection and extraction pipework and aggregate. Pipe material specifications, spacing gradients and sizing must be provided.		
	Note 22: The water balance must be designed to account for monthly inputs and outputs to demonstrate that the system will be able to operate in a satisfactory manner throughout the year. Cumulative leachate storage over multiple years of operation under average and wet conditions (at least two consecutive years) should also be factored in.		
	Note 23: Operators should use recognised water balance models to estimate leachate generation such as the https://example.com/Hydrologic Evaluation of Landfill Performance (HELP) model originally published by the United States Environmental Protection Agency and modified by Dr Klaus Berger at the University of Hamburg. The model should account for all predicted leachate inputs and outputs from the leachate management system.		
	Refer to Sections 5, 6 and 7 of the Environmental Assessment and Management Plan.		
	The Site is well established with a centralised leachate evaporation pond system, comprising four ponds with a combined operational capacity of approximately 60M. An assessment was undertaken using the Hydrologic Evaluation of Landfill Performance (HELP) model which concluded that existing capacity was sufficient, and that development of additional leachate ponds was not required (refer to Appendix F of the Environmental Assessment and Management Plan).		
2.13	Leachate pond design and construction.	\boxtimes	
	Provide details of the leachate pond design, including but not limited to:	<u> </u>	
	 pond dimensions and volumetric capacity²⁴ 		
	pond liner system:		
	o configuration of pond liner ²⁵		
	 statement of intended performance (overall permeability and containment features) 		
	 associated leachate conveyance infrastructure and equipment and connection points at the leachate pond(s) 		
	liner construction and/or installation ²⁶		
	• construction quality assurance (CQA) measures to be employed ²⁷ .		
	Design drawings of the liner system including that of the liner anchor trench must be provided (refer to Section 2.15 – Attachment 9).		
	Note 24: pond design must be determined based on the estimated leachate generation including all inputs and outputs. Refer to water balance requirements in Part 2.12.		
	Note 25: Refer to Part 2A for typical liner components – noting that where the leachate pond liner design differs from the landfill liner design, justification should be provided.		
	Note 26: Refer to Part 2A for construction and installation information requirements for pond liners.		

Part 2	2D: Leachate mana	gement			
	Note 27: Refer to Pa incorporated into the		QA requirements – CQA provisions for the pond liner can be A plan.		
	As discussed above additional leachate		isting capacity is sufficient to cater for Cell 7, development of not required.		
Attac	hments			N/A	Yes
2.14	Attachment 8: Figure/plan – layout of leachate management system	clearly of Multiple Refer to	a layout plan of the leachate management system which depicts all associated infrastructure and equipment. plans can be provided. the Figure 4 of the Environmental Assessment and ement Plan		\boxtimes
2.15	Attachment 9:	Detailed	d design drawings which clearly depict the following:		
	Detailed design drawings –	a)	Basal and side wall liner detail (typical section).	\boxtimes	
	leachate pond liner	b)	Inferred groundwater levels (mAHD) relative to the base of the leachate pond base (mAHD), depicted on cross-section drawings (showing at least 2 perpendicular planes on the horizontal, e.g. north-south, east-west, or as appropriate) showing perimeter side slopes/walls. All heights of the base, liner and the perimeter side walls should be shown in mAHD. Cross-sections must clearly demonstrate the separation distance between the lowest point of the leachate pond and underlying water table.		
		c)	Anchor trench detail.	\boxtimes	

Part 2E: Landfill gas management

- Fugitive landfill gas emissions can present a hazard to people and the environment. Landfill gas also
 contains many odorous trace gases which can cause degradation of amenity of nearby residential and
 industrial/commercial land uses.
- Prior to establishing a landfill facility, consideration should be given to the site's ability to control and manage landfill gas emissions.

	manago manami gao omicolono.	N/A	Yes
2.16	Landfill gas management system:		\boxtimes
	Provide details of the proposed landfill gas management system including:		
	 a detailed description of the proposed management system, installation procedures, installation timeline, monitoring, and maintenance procedures, including details on: 		
	 estimated gas generation rates across the entire lifespan of the landfill²⁸ 		
	 the containment measures to be implemented to reduce subsurface migration (e.g. installation of appropriate basal and capping liner systems) 		
	 the collection system (active or passive) and layout of landfill gas piping and extraction wells (vertical or horizontal or both), including details on installation processes and timeframes 		
	 utilisation of captured gas (e.g. flaring, treatment, and reuse in a system of a combustion) 		
	 specifications of combustion engines/flares and likely emissions (if relevant) 		
	 in-waste gas monitoring points, perimeter monitoring bores and associated monitoring program (refer also to Part 2G) 		
	 contingency plans in the event of breakdown of various components. 		
	Note 28: Landfill gas generation can be estimated using landfill gas generation models which take account of the potential quantity, rate and composition of the landfill gas generated.		
	Refer to Section 5 and Section 6 as well as Appendix E of the Environmental Assessment and Management Plan. Landfill gas generation modelling was not required since there is already an existing system in place.		
Attach	ments:	N/A	Yes

Part 2	E: Landfill gas ma	nagement	
2.17	Attachment 10: Drawings and	Design drawings and layout figure(s) of the proposed landfill gas management system including, but not limited to:	\boxtimes
	figures – landfill gas management	 in-cell layout of gas collection infrastructure (aerial and cross- section diagrams should be provided where relevant) 	
	system	 overview of associated above-ground gas management infrastructure 	
		landfill gas monitoring locations.	
		Multiple drawings and figures can be provided.	
		Refer to Appendix E of the Environmental Assessment and Management Plan	

Part 2F: Surface water management

NOTE:

- The premises must be designed and constructed to ensure that stormwater is diverted away from the landfill cell, leachate pond and other waste handling areas. This may be achieved through the use of surface grade changes, bunding, interceptor drains, piping and other drainage systems.
- Stormwater which has come into contact with waste materials must be collected and managed as leachate in the leachate management system.

		N/A	Yes
2.18	 Surface water management²⁹ Provide details on the proposed stormwater management strategies and controls for the landfill premises including, but not limited to: diversion of stormwater away from areas containing waste using drainage features, bunds, interceptor drains or other drainage systems details on clean stormwater holding ponds to be constructed (if required); design specifications and an overview of construction works should also be provided details of any proposed controlled releases of clean stormwater into the environment and/or proposed reuse options on-site erosion and sediment control along drainage lines and discharge points, including stormwater flow control, vegetation, detention ponds, minimising land disturbance, and other temporary and permanent erosion protection measures. Note 29: Guidance on stormwater management can be found in DWER's <u>Stormwater Management Manual for Western Australia</u>. Refer to Section 5 and Section 6 of the Environmental Assessment and Management Plan Given that the Site is well established with an extensive stormwater network system, no new stormwater dams are proposed for the development of Cell 7. 		
Attacl	nments:	N/A	Yes
2.19	Attachment 11: Drawings and figures – surface water management infrastructure Design drawings and layout figure(s) of the proposed surface water management infrastructure. Refer to the Drawing set in Appendix A of the Environmental Assessment and Management Plan		

Part 2G: Monitoring requirements

- A comprehensive monitoring program should be developed to support the ongoing operation of a landfill facility. Aspects that should be included in the program (as a minimum) include leachate, landfill gas, surface water and groundwater. Odour monitoring should also be considered, depending on the environmental siting.
- The operator must continually review the positioning of monitoring points during the regular review of monitoring data, and as the landfill facility expands consideration must be given to expanding the monitoring network to reflect the design proposals (and refinement of the CSM).
- Typical monitoring aspects are outlined further below. Where an operator elects not to commit to certain monitoring programs, they must provide clear justification and rationale for this decision.

		Yes	N/A
2.20	Leachate quality monitoring Provide details of the proposed leachate quality monitoring program (refer also to Part 2D), including, but not limited to, sampling locations, sampling methodology, analysis suite, sampling frequency, and reporting requirements. Refer to the Site Licence L8871/2014/2		
2.21	Landfill gas monitoring Provide details on the proposed landfill gas monitoring program (refer also to Part 2E), including, but not limited to, sampling locations, well/monitoring point construction specifications, sampling methodology, analysis suite, sampling frequency and reporting requirements.	\boxtimes	

Part 2	G: Monitoring requirements			
	Proposed sampling locations should give regard to the landfill surface, subsurface (inwaste), perimeter, subsurface services on and adjacent to the site, buildings or structure on and adjacent to the site, and landfill gas treatment/management infrastructure (such flares and combustion engines).			
	Action levels for different monitoring locations must be documented to outline what action will be taken to address the matter and/or what further monitoring will be carried out to verify the effectiveness of corrective actions.	on		
	Refer to Section 5 and Section 6 and Appendix E of the Environmental Assessment and Management Plan. The landfill gas management system will be managed by the specialist landfill gas contractor.	ł		
2.22	Groundwater and surface water monitoring		\square	
	Provide details on the proposed groundwater and surface water monitoring program, including, but not limited to:		\boxtimes	Ш
	sampling locations			
	well construction specificationssampling methodology			
	sampling methodology analysis suite			
	sampling frequency			
	reporting requirements.			
	The monitoring program should as a minimum seek to establish:			
	 the background groundwater quality and levels (in mAHD and mBGL) the background surface water quality and levels/flow rates and flow direction the local aquifers, and groundwater flow direction and rates of each aquifer a monitoring network that acts as an early indicator of leachate contamination in groundwater or surface water prior to offsite migration. 			
	For a new facility, the operator should seek to demonstrate baseline groundwater and/o surface water conditions prior to construction works and to feed the results of this monitoring into the initial CSM development.	r		
	A sampling and analysis quality plan (SAQP) should be prepared to ensure that the data collected is representative and sufficient to address critical gaps and uncertainties identified in the CSM so that the information obtained provides a reliable basis for continually reviewing site operations and meeting compliance requirements of the operating licence.	а		
	Further guidance on developing a groundwater and surface monitoring program, including the development of a SAQP, can be sourced from DWER's <u>Assessment and management of contaminated sites guideline</u> and from Schedule B2 of the <u>National Environment Protection (Assessment of Site Contamination) Measure 1999</u> (NEPM).	ng		
	Refer to the Site Licence L8871/2014/2.			
Attach	nments:		N/A	Yes
2.23	Attachment 12: Applicants must document the proposed monitoring program in a land monitoring plan or a series of equivalent standalone monitoring and/or management plans.		\boxtimes	
	The SAQP required in Part 2.22 should be incorporated in this plan.			
	Refer to Sections 5 and 6 of the Environmental Assessment & Management Plan as well as the Site Licence L8871/2014/2.			

Part 3: Premises operations

- In addition to the landfill design and construction, operational practices play an integral role in the protection of the environment.
- This section outlines the operational management aspects that must be addressed as part of an application. Focus should be given to the day-to-day activities which are undertaken at the facility and the practices to be implemented to minimise amenity and environmental impacts.

		N/A	Yes
3.1	Landfill management and operations		Z
	Provide operational detail on the following operational aspects:		

Part 3: Premises operations operational hours of the facility security fencing and site access internal traffic control details on weighbridge for monitoring waste acceptance waste acceptance,30 including details of acceptance and handling requirements for different waste types (e.g. putrescibles, asbestos waste, special waste types, contaminated solid wastes, etc.) and record keeping landfilling method/waste placement, filling sequence and tipping face management (the vertical and horizontal size of the tipping face must be specified). waste cover³¹ (details on daily, intermediate and final cover, materials to be used, volumes required and storage area pre-use), litter and debris control (measures to prevent the discharge of litter and debris beyond the active landfill area and greater premises boundary) dust management - measures to prevent operations impacting environmental values and social surroundings odour management - measures to protect environmental values and social surroundings from unreasonable emissions of odour noise management - demonstrate and maintain compliance with the assigned levels specified in the Environmental Protection (Noise) Regulations 1997 (Noise Regulations) fire prevention and management (measures to minimise the risk of fires occurring at the facility) and emergency response procedures for fire and other emergencies (e.g. spills, landfill gas emergencies, etc.) vector management (measures to prevent the attraction, refuge, growth and spread of vermin and pests to mitigate impacts to environmental values and social surroundings) chemical and fuel stores, including details of storage requirements environmental monitoring (refer to Part 2G)32 contingency planning (map out all likely incidents and document appropriate corrective measures). Note 30: Information must be consistent with the requirements outlined in Part 8 (Emissions, discharges, and waste) of the main application form i.e. wastes must be described in accordance with the Landfill Waste Classifications and Waste Definitions 1996. Note 31: Alternative daily and interim cover materials can be proposed but must be supported by details of the physical and chemical properties of the alternative cover together with information on how it will achieve the same or better performance outcomes, taking into consideration seasonal Note 32: Reference can be made to the information provided against Part 2G of this checklist. Refer to Section 6 and Section 7 of the Environmental Assessment & Management Plan as well as the Site Licence L8871/2014/2. **Attachments:** N/A Yes 32 Attachment Applicants must document the operational management aspects in a X13: Landfill consolidated landfill environmental management plan (LEMP).33 The environmental landfill monitoring plan (required by part 2G) can form part of the LEMP. management Note 33: The LEMP is a dynamic document and must be reviewed on a regular plan basis as management and operational practices change at the facility. The LEMP

Part 4: Landfill closure and rehabilitation		
NOTE: Landfill closure, rehabilitation and aftercare management must be planned and consider design concept for the landfill facility.	ed in the i	nitial
	N/A	Yes

Refer to Section 6 and Section 7 of the Environmental Assessment &

should be made available to all operational staff and used in training.

Management Plan as well as the Site Licence L8871/2014/2.

Part 4: Landfill closure and rehabilitation Provide information about the proposed closure and aftercare management of the facility, including, but not limited to: details of future intended land use details of progressive closure, capping and rehabilitation of used cells on the premises final landform and surface contours (pre- and post-settlement) for each landfill cell(s) which forms the scope of the application; a discussion on the final landform in the context of surrounding topography must also be provided landfill cap design detail and drawings (specifications and materials to be used in the final cap) - where geomembranes are proposed to be used in a capping system, similar design detail to that provided in Part 2B (landfill liner specifications) must be submitted (see Section 4.2 - Attachment 14) design detail for connections in the cap to landfill gas and/or leachate collection and monitoring points (where relevant) stormwater management measures for water shed from the cap and final landform construction quality assurance (CQA) measures to be employed in cap construction/installation details on post-closure monitoring and aftercare management³⁴ (details of proposed environmental monitoring must be consistent with the information requirements outlined in Part 2G) Note 34: Post-closure monitoring and aftercare management must include inspections of the cap and surveillance of differential settlement to verify continually the integrity of the landfill cap. Refer to Sections 5 and 8 of the Environmental Assessment & Management Plan as well as the Site Licence L8871/2014/2. Attachments: N/A Yes Attachment 14: Applicants must document the proposed objectives and closure and \boxtimes rehabilitation measures (as required by Part 4.1) in a consolidated Landfill closure plan (including landfill closure plan (LCP). design figures) Within the plan the following drawings/figures must be provided: final contour map – depicting proposed final contours, top & side slopes, and surface drainage features typical cross-sections of the proposed landfill cap and design (refer to Part 2A for liner design/construction information requirements - the same should be followed for the capping location of passive gas and leachate management infrastructure intended to remain on the premises throughout LCP to be provided 3 months prior to filling cell in accordance with Site Licence L8871/2014/2.