

Licence number L8495/2010/2

Licence holder Mount Gibson Mining Limited

ACN 074 575 885

Registered business address Level 1, 2 Kings Park Road

WEST PERTH WA 6005

DWER file number 2010/009798-3

Duration 21/01/2014 to 20/01/2031

Date of issue 16/01/2014 **Date of amendment** 09/11/2023

Premises details Extension Hill Mine Site

PAYNES FIND WA 6612

Legal description -

Mining Tenements G59/30, G59/33, G59/34, L59/68, L59/69, L59/87, M59/338, M59/339 and

M59/526, M59/454, M59/455 and M59/609

As depicted in Schedule 1.

Prescribed premises category description (Schedule 1, Environmental Protection Regulations 1987)	Assessed production / design capacity
Category 5: Processing or beneficiation of metallic or non-metallic ore:	5 000 000 tonnes per annual period
Category 63: Class I Inert Landfill site	12 000 tonnes per annual period
Category 64: Class II putrescible landfill site	150 tonnes per annual period
Category 85: Sewage facility	48 cubic metres per day

This licence is granted to the licence holder, subject to the attached conditions, on 09 November 2023, by:

Melissa Chamberlain A/MANAGER, RESOURCE INDUSTRIES **REGULATORY SERVICES**

an officer delegated under section 20 of the Environmental Protection Act 1986 (WA)

Licence History

Date	Reference number	Summary of changes	
20/01/2011	L8495/2010/1	Licence issued	
13/10/2011	L8495/2010/1	Licence amendment for general condition updates	
30/08/2012	L8495/2010/1	Licence amendment for landfill conditions	
20/06/2013	L8495/2010/1	Licence amendment for dust suppression conditions	
07/11/2013	L8495/2010/1	Licence amendment to update conditions	
12/12/2013	L8495/2010/1	Licence amendment for condition changes	
16/01/2014	L8495/2010/2	Licence reissue and REFIRE conversion	
01/05/2014	L8495/2010/2	Licence amendment for production increase and condition upgrade	
29/04/2016	L8495/2010/2	This notice was given in accordance with section 59B(9) of the <i>Environmental Protection Act 1986</i> to the new expiry date of the licence.	
09/06/2017	L8495/2010/2	Amendment Notice 1 - To extend premises boundary to include an additional Category 64 landfill for Iron Hill project operations.	
03/01/2019	L8495/2010/2	Amendment Notice 2 - For additional short term Cat 64 landfilling at the ROM pad and addition of Category 63 for insitu burial of decommissioned road.	
09/11/2023	L8495/2010/2		

Interpretation

In this licence:

- (a) the words 'including', 'includes' and 'include' in conditions mean "including but not limited to", and similar, as appropriate;
- (b) where any word or phrase is given a defined meaning, any other part of speech or other grammatical form of that word or phrase has a corresponding meaning;
- (c) where tables are used in a condition, each row in a table constitutes a separate condition;

- (d) any reference to an Australian or other standard, guideline, or code of practice in this licence:
 - (i) if dated, refers to that particular version; and
 - (ii) if not dated, refers to the latest version and therefore may be subject to change over time;
- (e) unless specified otherwise, any reference to a section of an Act refers to that section of the EP Act; and
- (f) unless specified otherwise, all definitions are in accordance with the EP Act.

NOTE: This licence requires specific conditions to be met but does not provide any implied authorisation for other emissions, discharges, or activities not specified in this licence.

Licence Conditions

Premises operation

1. The Licence Holder must ensure the limits specified in Table 1 are not exceeded.

Table 1: Production or design capacity limits

Category ¹	Category description	Premises production or design capacity limit	
5	Processing or beneficiation of metallic or non-metallic ore	5,000,000 tonnes per annual period	
85	Sewage facility	48 cubic metres per day	

Note 1: Environmental Protection Regulations 1987, Schedule 1

- 2. The Licence Holder must only accept waste to a landfill if:
 - (a) it is of a type listed in Table 2;
 - (b) the quantity accepted is below any quantity limit listed in Table 2; and
 - (c) it meets any specification listed in Table 2.

Table 2: Waste acceptance

Category 63 landfill waste type	Quantity limit tonnes/year	Specification
Inert Waste Type 1	12,000 tonnes per annual period	Demolition materials from decommissioning works (primarily concrete slabs and footers) and broken up decommissioned road Waste containing visible asbestos or ACM must not be accepted
Category 64 landfill Waste type	Quantity limit tonnes/year	Specification ¹
Inert Waste Type 1	150 tonnes per annual	Waste containing visible asbestos or

	period	ACM must not be accepted	
Inert Waste Type 2		Non-biodegradable organic materials	
Putrescible Waste		None Specified	
Special Waste Type 2		Biomedical/ clinical	
Contaminated Solid Waste		Must meet the acceptance criteria for Class II landfill	

Note 1: Additional requirements for the acceptance of controlled waste (including asbestos and tyres) are set out in the *Environmental Protection (Controlled Waste) Regulations 2004*.

- 3. The Licence Holder must ensure that where waste does not meet the waste acceptance criteria set out in condition 2 it is removed from the Premises by the delivery vehicle or, where that is not possible, stored in a segregated storage area or container and removed to an appropriately authorised facility as soon as practicable.
- 4. The Licence Holder must ensure that wastes accepted onto a landfill and wastewater treatment plant are only subjected to the processes set out in Table 3 and in accordance with any process limits described in that Table.

Table 3: Waste processing

Landfill and waste type	Process(es)	Process limits ^{1, 2}
Category 63 landfills	Receipt, handling and	Disposal of Inert Waste Type 1 by landfilling must only take place within the landfill areas shown on Figure 1 and Figure 2.
	disposal of waste by landfilling	The landfill as shown in Schedule 1, Figure 2 must have a single earthen barrier above the HDPE lining prior to the first disposal.
	i anaming	Water that has come in contact with waste must be retained at the landfills.
Category 64 landfill – base of		Disposal of Inert Waste Type 1 and Inert Waste Type 2 (tyres) only in the landfill area shown in Figure 1.
the ROM pad		The tipping area must be no greater than 30 metres in length.
		Tyres to be stored in piles of up to 100 units with a 6m separation distance between piles.
Category 64 landfill - top of		Disposal of waste by landfilling must only take place within the landfill areas shown in Schedule 1, Figure 1.
the ROM pad and open landfills		The landfill must be within an area enclosed by earthen bunds or fencing at least 2 metres in height, to provide an effective barrier to horses or stock and to contain windblown litter.
		Waste must be disposed of in a defined trench.
		The tipping area must be no greater than 30 metres in length.
		Surface water drainage must be designed and maintained to divert surface water runoff away from areas where there is waste; and water that has come in contact with waste shall must be retained on the landfill.
		Waste must not be burnt at the landfill area.

Landfill and waste type	Process(es)	Process limits ^{1, 2}
		A firebreak of at least 3 metres must be maintained around the landfill.
		The separation distance between the base of the landfill and the highest groundwater level must not be less than 3 metres.
		Special Waste Type 2:
		Only to be disposed of into a designated biomedical waste disposal area within the landfill.
		Not to be deposited within 2m of the final tipping surface of the landfill.
		No works must be carried out on the landfill that could lead to biomedical wastes being excavated or uncovered.
Sewage	Wastewater treatment plant	Biological and physical treatment

Note 1: Requirements for landfilling tyres are set out in Part 6 of the *Environmental Protection Regulations1987*. Note 2: Additional requirements for the acceptance and landfilling of controlled waste (including asbestos and tyres) are set out in the *Environmental Protection (Controlled Waste) Regulations 2004*.

- **5.** The Licence Holder must manage the landfilling activities to ensure:
 - (a) waste is placed to ensure all faces are stable and capable of retaining rehabilitation material; and
 - (b) rehabilitation of a cell or phase takes place within 6 months after disposal in that cell or phase has been completed.
- 6. The Licence Holder must ensure that cover is applied and maintained on all accessible waste in accordance with Table 4 and that sufficient stockpiles of cover are maintained on site at all times.

Table 4: Cover requirements¹

Waste Type	Material	Depth	Timescales
Inert Waste Type 1	Dense, inert and incombustible	200mm	Monthly or as soon as practicable after deposit.
Putrescible Waste	material or such other material as is approved in	500mm	Monthly or as soon as practicable after deposit.
Inert Waste Type 2	respect of a particular landfill site, and totally covered.	200mm	To be covered by the end of the working day in which the waste was deposited with sufficient quantities of Type 1 inert waste or clean fill to prevent the spread of fire and harbouring of disease vectors.
Special Waste Type 2		100mm	As soon as practicable after deposit prior to compaction.
Contaminated solid wastes		200mm	Fortnightly or as soon as practicable after deposit.

Note 1: Additional requirements for the covering of tyres are set out in Part 6 of the *Environmental Protection Regulations 1987*.

7. The Licence Holder must ensure that wind-blown waste is contained within the boundary

- of the landfill and that wind-blown waste is returned to the tipping area on at least a monthly basis.
- **8.** The Licence Holder must ensure that wastewater and sewage sludge is only stored and/or treated within vessels or compounds provided within the infrastructure detailed in Table 5.
- 9. The Licence Holder must ensure that effluent is only discharged into containment ponds with the relevant infrastructure requirements and at the locations specified in Table 5 and identified in Schedule 1.

Table 5: Containment infrastructure

Storage vessel or compound	Material Infrastructure details	
Sewage evaporation pond	Wastewater	Clay lined to achieve a permeability of at least <1x10 ⁻⁹ m/s or equivalent

- **10.** The Licence Holder must manage containment cells and/or dams or ponds and/or turkey's nests in Table 5 such that:
 - (a) a minimum top of embankment freeboard of 300mm or a 1 in 100 year/72 hour storm event (whichever is greater) is maintained; and,
 - (b) methods of operation minimise the likelihood of erosion of the embankments by wave action.
- 11. The Licence Holder must ensure that any discharge of water from the operational and wash down areas must be discharged via fuel/oil traps and silt traps.
- **12.** The treated washdown bay water must only be used for dust suppression on the iron ore stockpiles.

Emissions

Emissions to land

13. The Licence Holder must not cause or allow emissions to land greater than the limits listed in Table 6

Table 6: Emission limits to land

Emission point reference	Parameter	Limit (including units)	Averaging period
Outlet pipe from the washdown bay treated wastewater	Total Recoverable Hydrocarbons	10mg/L	Spot sample

Monitoring

General monitoring

- **14.** The Licence Holder must ensure that:
 - (a) all water samples are collected and preserved in accordance with AS/NZS 5667.1:
 - (b) all wastewater samples are collected in accordance with AS/NZS 5667.10; and

- (c) all laboratory samples are submitted to and tested by a laboratory with current NATA accreditation for the parameters being measured.
- **15.** The Licence Holder must ensure that quarterly monitoring is undertaken at least 45 days apart.
- **16.** The Licence Holder must ensure that all monitoring equipment used on the Premises to comply with the conditions of this Licence is calibrated in accordance with the manufacturer's specifications.
- 17. The Licence Holder must, where the requirements for calibration cannot be practicably met, or a discrepancy exists in the interpretation of the requirements, bring these issues to the attention of the CEO accompanied with a report comprising details of any modifications to the methods.

Monitoring of emissions to land

18. The Licence Holder must undertake the monitoring in Table 7 according to the specifications in that table.

Table 7: Monitoring of emissions to land

Emission point reference	Parameter	Units	Frequency
Outlet pipe from the washdown bay treated wastewater storage tank	Total Recoverable Hydrocarbons (TRH)	mg/L	Quarterly

- **19.** The Licence Holder must keep a written or electronic record of all contaminated solid wastes accepted for burial at the premises. The record should include but not be limited to:
 - (a) the time and date the waste was received;
 - (b) the type of contaminated solid waste;
 - (c) the nature of the contaminated solid waste;
 - (d) the quantity of the contaminated solid waste;
 - (e) the disposal location by grid reference; and
 - (f) the source of the contaminated solid waste.

Process monitoring

- **20.** The Licence Holder must include in the Environmental Report required by condition 23:
 - (a) the total volume of wastewater used for dust suppression during the reporting period; and
 - (b) the results from the wastewater sampling.

Records and Reporting

- 21. The Licence Holder must record the following information in relation to complaints received by the licence holder (whether received directly from a complainant or forwarded to them by the Department or another party) about any alleged emissions from the premises:
 - (a) the name and contact details of the complainant, (if provided);

- (b) the time and date of the complaint;
- (c) the complete details of the complaint and any other concerns or other issues raised; and
- (d) the complete details and dates of any action taken by the licence holder to investigate or respond to any complaint.

22. The Licence Holder must

- (a) undertake an audit of their compliance with the conditions of this licence during the preceding annual period; and
- (b) prepare and submit to the CEO by no later than 60 days after the end of that annual period an Annual Audit Compliance Report in the approved form.
- 23. The Licence Holder must submit to the CEO an Environmental Report by 31 October 2023 and biennially thereafter. The report shall contain the monitoring results and data collected as a requirement of any condition and set out in Table 8 of this licence.

Table 8: Environmental Report

Condition	Requirement
-	Summary of any failure or malfunction of any pollution control equipment and any environmental incidents that have occurred during the annual period and any action taken
1, 2 and 13	Limit exceedances
18	Monitoring of emissions to land
19	Contaminated solid waste records
20	Wastewater monitoring
21	Incidents and Complaints summary

- **24.** The Licence Holder must ensure that the Environmental Report also contains:
 - (a) any relevant process, production or operational data recorded under condition 16;
 - (b) an assessment of the information contained within the report against previous monitoring results and Licence limits; and
 - (c) a list of any original monitoring reports submitted to the Licence Holder from third parties for the annual period and make these reports available on request.
- **25.** The Licence Holder must maintain accurate and auditable books including the following records, information, reports, and data required by this licence:
 - (a) the calculation of fees payable in respect of this licence:
 - (b) any maintenance of infrastructure that is performed in the course of complying with the conditions of this licence; and
 - (c) complaints received under condition 21 of this licence.
- **26.** The books specified under condition 25 must:
 - (a) be legible;
 - (b) if amended, be amended in such a way that the original version(s) and any

- subsequent amendments remain legible and are capable of retrieval;
- (c) be retained by the licence holder for the duration of the licence; and
- (d) be available to be produced to an inspector or the CEO as required.

END OF CONDITIONS

Definitions

In this licence, the terms in

Table 9 have the meanings defined.

Table 9: Definitions

Term	Definition
ACM	asbestos containing material
ACN	Australian Company Number
Annual Audit Compliance Report (AACR)	means a report submitted in a format approved by the CEO (relevant guidelines and templates may be available on the Department's website).
annual period	a 12 month period commencing from 01 October until 30 September of the immediately following year.
AS/NZS 3816	means the Australia Standard AS/NZS 3816:1998 Management of clinical and related wastes
AS/NZS 5667.1	means the Australian Standard AS/NZS 5667.1 Water Quality – Sampling – Guidance of the Design of sampling programs, sampling techniques and the preservation and handling of samples
AS/NZS 5667.10	means the Australian Standard AS/NZS 5667.10 Water Quality – Sampling – Guidance on sampling of waste waters
asbestos	means the asbestiform variety of mineral silicates belonging to the serpentine or amphibole groups of rock-forming minerals and includes actinolite, amosite, anthophyllite, chrysolite, crocidolite, tremolite and any mixture containing 2 or more of those
asbestos fibres	has the meaning defined in the Guidelines for Assessment, Remediation and Management of Asbestos Contaminated Sites, Western Australia, (DOH, 2009)
averaging period	means the time over which a limit or target is measured or a monitoring result is obtained
books	has the same meaning given to that term under the EP Act.

Department of Water and Environmental Regulation

Term	Definition
CEO	means Chief Executive Officer of the Department.
	"submit to / notify the CEO" (or similar), means either:
	Director General Department administering the Environmental Protection Act 1986 Locked Bag 10 Joondalup DC WA 6919
	or:
	info@dwer.wa.gov.au
clean fill	as defined in the Landfill Definitions.
controlled wase	has the definition in <i>Environmental Protection (Controlled Waste) Regulations</i> 2004.
Department	means the department established under section 35 of the <i>Public Sector Management Act 1994</i> (WA) and designated as responsible for the administration of the EP Act, which includes Part V Division 3.
discharge	has the same meaning given to that term under the EP Act.
emission	has the same meaning given to that term under the EP Act.
EP Act	Environmental Protection Act 1986 (WA).
EP Regulations	Environmental Protection Regulations 1987 (WA).
HPDE	means high density polyethylene.
Inert Waste Type 1	as defined in the Landfill Definitions.
Inert Waste Type 2	as defined in the Landfill Definitions.
Landfill Definitions	means the Landfill Waste Classification and Waste Definitions 1996 (as amended 2018).
licence	refers to this document, which evidences the grant of a licence by the CEO under section 57 of the EP Act, subject to the specified conditions contained within.
licence holder	refers to the occupier of the premises, being the person specified on the front of the licence as the person to whom this licence has been granted.
NATA	means the National Association of Testing Authorities, Australia.
NATA accredited	Means in relation to the analysis of a sample that the laboratory is NATA accredited for the specified analysis at the time of the analysis.
premises	refers to the premises to which this licence applies, as specified at the front of this licence and as shown on the premises map Figure 1 in Schedule 1 to this licence.
prescribed premises	has the same meaning given to that term under the EP Act.

Term	Definition
Putrescible Waste	as defined in the Landfill Definitions.
ROM	means Run of Mine
Special Waste Type 2	as defined in the Landfill Definitions.
Spot sample	means a discrete sample representative at the time and place at which the sample is taken
waste	has the same meaning given to that term under the EP Act.
Waste Type	identified in the Landfill Definitions, or in Schedule 1 of the <i>Controlled Waste Regulations 2004</i> (as applicable).

Schedule 1: Maps

Premises Map

The Premises boundary and infrastructure is shown in the map below. The outer blue line depicts the premises boundary. The green line depicts the location of Category 63 landfilling. The green hatched area depicts the location of the new Category 64 landfill.




Figure 1: Premises Map




Figure 2: Category 63 additional Landfill locations for Inert Waste Type 1