



|                                    |                                                                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <b>Works approval number</b>       | W2872/2025/1                                                                                                                        |
| <b>Works approval holder</b>       | Kalgoorlie Consolidated Gold Mines Pty Ltd                                                                                          |
| <b>ACN</b>                         | 009 377 619                                                                                                                         |
| <b>Registered business address</b> | Level 4, 500 Hay Street<br>SUBIACO WA 6008                                                                                          |
| <b>DWER file number</b>            | APP-0026907                                                                                                                         |
| <b>Duration</b>                    | 23/10/2025 to 22/10/2028                                                                                                            |
| <b>Date of issue</b>               | 21/10/2025                                                                                                                          |
| <b>Premises details</b>            | Fimiston Processing Plant<br>Black Street, KALGOORLIE WA 6430<br>Legal description<br>Mining tenements M26/308, M26/778 and M26/725 |

| <b>Prescribed premises category description</b><br>(Schedule 1, <i>Environmental Protection Regulations 1987</i> ) | <b>Assessed production / design capacity</b> |
|--------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Category 5: Processing or beneficiation of metallic or non-metallic ore                                            | 27,000,000 tonnes per annual period          |

This works approval is granted to the works approval holder, subject to the attached conditions, on 23 October 2025, by:

**MANAGER, RESOURCE INDUSTRIES**

**STATEWIDE DELIVERY (ENVIRONMENTAL REGULATION)**

an officer delegated under section 20 of the *Environmental Protection Act 1986* (WA)

## Works approval history

| Date            | Reference number | Summary of changes                                                                           |
|-----------------|------------------|----------------------------------------------------------------------------------------------|
| 23 October 2025 | W2872/2025/1     | Works approval granted for the construction and time limited operations of Fimiston III TSF. |

## Interpretation

In this works approval:

- (a) the words 'including', 'includes' and 'include' in conditions mean "including but not limited to", and similar, as appropriate.
- (b) where any word or phrase is given a defined meaning, any other part of speech or other grammatical form of that word or phrase has a corresponding meaning.
- (c) where tables are used in a condition, each row in a table constitutes a separate condition.
- (d) any reference to an Australian or other standard, guideline, or code of practice in this works approval:
  - (i) if dated, refers to that particular version; and
  - (ii) if not dated, refers to the latest version and therefore may be subject to change over time.
- (e) unless specified otherwise, any reference to a section of an Act refers to that section of the EP Act; and
- (f) unless specified otherwise, all definitions are in accordance with the EP Act.

**NOTE:** This works approval requires specific conditions to be met but does not provide any implied authorisation for other emissions, discharges, or activities not specified in this works approval.

# Works approval conditions

The works approval holder must ensure that the following conditions are complied with:

## Construction phase

### Infrastructure and equipment

1. The works approval holder must:
  - (a) construct the critical containment infrastructure.
  - (b) in accordance with the corresponding design and construction requirements; and
  - (c) at the corresponding infrastructure location as set out in Table 1.

**Table 1: Critical containment infrastructure design and construction requirements**

|    | Infrastructure                        | Design and construction requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Infrastructure location          |
|----|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| 1. | Fimiston III TSF - starter embankment | <ul style="list-style-type: none"><li>• Height of Fimiston III TSF starter embankment maximum of 10 m (396.5 m RL), constructed as per design shown in Figure 3 and Figure 4.</li><li>• An underdrainage system beneath the TSF floor along the upstream toe of the starter embankment on the down-gradient side of the TSF, and at the supernatant pond location. Comprising of a series of perforated collection pipes encompassed by a dual filter system. Constructed with a nominal grade to facilitate gravity flow towards the lowest section of the embankment footprint for collection, as shown in Figure 5.</li><li>• Starter embankment constructed such that the fill will be moisture conditioned to a minimum of -1 / +2% of the optimum moisture content, placed in 300 mm thick layers and compacted to a minimum of 98% standard maximum dry density.</li><li>• Decant access causeway constructed such that the fill will be moisture conditioned to a minimum of <math>\pm 2\%</math> of the optimum moisture content, placed in 500 mm thick layers and compacted to a minimum of 95% standard maximum dry density.</li><li>• Turret system decant with skid mounted surface pump.</li><li>• The minimum top of embankment freeboard of 300 mm marked.</li><li>• Surface water diversion channel to the north and south of the TSF.<ul style="list-style-type: none"><li>○ Sufficient to divert peak flows associated with the selected 1:100 AEP (1%) design event, approximately 284 m<sup>3</sup>/s</li></ul></li></ul> | As shown in Schedule 1: Figure 1 |

|    | Infrastructure                                      | Design and construction requirements                                                                                                                                                                                                                           | Infrastructure location                                                 |
|----|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
|    |                                                     | <ul style="list-style-type: none"> <li>Minimum cut depth 1.6 m (north channel), 1.3 m (south channel)</li> <li>Minimum base width: ~4 m</li> <li>Engineered external toe drains to capture incidental rainfall on outer TSF slopes.</li> </ul>                 |                                                                         |
| 2. | Pipelines carrying tailings and decant return water | <ul style="list-style-type: none"> <li>Equipped with automatic cut-outs in the event of a pipe failure; or</li> <li>Provided with secondary containment sufficient to contain any spill for a period equal to the time between routine inspections.</li> </ul> | Installed within the pipeline corridor as shown in Schedule 1: Figure 2 |

### Construction of groundwater monitoring wells


2. The works approval holder must design, construct, and install groundwater monitoring wells in accordance with the requirements specified in Table 2.

**Table 2: Infrastructure requirements – groundwater monitoring bores**

| Infrastructure               | Design, construction, and installation requirements                                                                                                                                                                                                                                                                                                                                                                                                        | Monitoring well location(s)                                          |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| Groundwater monitoring bores | <u>Well design and construction:</u><br>Designed and constructed in accordance with <i>ASTM D5092/D5092M-16: Standard practice for design and installation of groundwater monitoring bores</i> .<br>Well screens must target the part, or parts, of the aquifer most likely to be affected by contamination <sup>1</sup> .<br>Where temporary/seasonal perched features are present, wells must be nested, and the perched features individually screened. | Indicative locations identified as “Monitoring bores” in Schedule 1, |
|                              | <u>Logging of borehole:</u><br>Soil samples must                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                      |

| Infrastructure | Design, construction, and installation requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Monitoring well location(s) |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
|                | <p>be collected and logged during the installation of the monitoring wells.</p> <p>A record of the geology encountered during drilling must be described and classified in accordance with the Australian Standard Geotechnical Site Investigations AS1726.</p> <p>Any observations of staining / odours or other indications of contamination must be included in the bore log.</p> <p><u>Well construction log:</u></p> <p>Well construction details must be documented within a well construction log to demonstrate compliance with <i>ASTM D5092/D5092M-16</i>.</p> <p>The construction logs shall include elevations of the top of casing position to be used as the reference point for water-level measurements, and the elevations of the ground surface protective installations.</p> <p><u>Well development:</u></p> <p>All installed monitoring wells must be developed after drilling to remove fine sand, silt, clay and any drilling mud residues from</p> |                             |

| Infrastructure | Design, construction, and installation requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Monitoring well location(s)                                          |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
|                | <p>around the well screen to ensure the hydraulic functioning of the well. A detailed record should be kept of well development activities and included in the well construction log.</p> <p><u>Installation survey:</u> the vertical (top of casing) and horizontal position of each monitoring well must be surveyed and subsequently mapped by a suitably qualified surveyor.</p> <p><u>Well network map:</u> a well location map (using aerial image overlay) must be prepared and include the location of all monitoring wells in the monitoring network and their respective identification numbers.</p> | Indicative locations identified as “Monitoring bores” in Schedule 1, |



| Infrastructure | Design, construction, and installation requirements | Monitoring well location(s) |
|----------------|-----------------------------------------------------|-----------------------------|
|                |                                                     | Figure 6<br>(13 bores)      |

Note 1 refer to Section 8 of Schedule B2 of the *Assessment of Site Contamination NEPM* for guidance on well screen depth and length.

3. The works approval holder must, within 90 calendar days of the monitoring wells being constructed, submit to the CEO a well construction report evidencing compliance with the requirements of condition 2.

### Construction of seepage recovery bores

4. The works approval holder must design, construct and install the Stage 1 production bores in accordance with the requirements specified in Table 3.

**Table 3: Infrastructure requirements – production bores**

| Infrastructure                                                             | Design and construction/installation requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Seepage recovery bore locations                                                                              |
|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Stage 1 production bores for recovery of seepage from the Fimiston III TSF | <ul style="list-style-type: none"> <li>Four production bores will be installed during the construction stage of Fimiston III TSF</li> <li>The installed pumping capacity in each bore between 0.5 L/s and 1.0 L/s.</li> <li>Bore construction depths to average 30 m.</li> <li>Installation of seepage recovery bores by a suitably qualified hydrogeologist.</li> <li>Drilling and construction of the seepage recovery bores will be in accordance with the <i>Minimum Construction Requirements for Water Bores in Australia</i><sup>1</sup>.</li> <li>The vertical (top of casing) and horizontal position of each seepage recovery bore must be surveyed and subsequently mapped by a suitably qualified surveyor.</li> <li>A seepage recovery bore location map (using aerial image overlay) must be prepared and include the location of all seepage recovery bores and their respective identification numbers.</li> </ul> | The number and location of Stage 1 production bores to be determined by a suitably qualified hydrogeologist. |

Note 1 refer to *Minimum Construction Requirements for Water Bores in Australia* Fourth Edition published by National Uniform Drillers Licensing Committee 2020

### Compliance reporting (critical containment infrastructure)

5. The works approval holder must within 90 calendar days of the Critical Containment Infrastructure identified by condition 1 being constructed:
  - (a) undertake an audit of their compliance with the requirements of condition 1, and

- (b) prepare and submit to the CEO a Critical Containment Infrastructure Report on that compliance.
6. The Critical Containment Infrastructure Report required by condition 5 must include as a minimum the following:
- (a) certification by a suitably qualified geotechnical engineer that each item of critical containment infrastructure or component thereof, as specified in condition 1, has been built and installed in accordance with the requirements specified in condition 1.
  - (b) as constructed plans and a detailed site plan showing the location and dimensions for each item of critical containment infrastructure or component thereof, as specified in condition 1.
  - (c) photographic evidence of the installation of the infrastructure.
  - (d) be signed by a person authorised to represent the works approval holder and contains the printed name and position of that person; and
  - (e) include monitoring data indicating the baseline ambient environmental conditions at the premises prior to and immediately following construction of Fimiston III TSF.
7. The monitoring of the baseline ambient environmental conditions required under condition 6(e) must be undertaken in accordance with the requirements of Table 4.

**Table 4: Determination of baseline ambient environmental conditions**

| Parameter       | Monitoring location                                                             | Unit    | Frequency                                                                  | Averaging period | Method                            |                                  |
|-----------------|---------------------------------------------------------------------------------|---------|----------------------------------------------------------------------------|------------------|-----------------------------------|----------------------------------|
|                 |                                                                                 |         |                                                                            |                  | Sampling                          | Analysis                         |
| SWL             | All proposed monitoring bores as established under condition 2 of this licence. | mbgl    | Prior to the commencement of deposition of tailings into Fimiston III TSF. | Spot sample      | In accordance with AS/NZS 5667.11 | In accordance with AS/NZS 5667.1 |
| pH <sup>1</sup> |                                                                                 | -       |                                                                            |                  |                                   |                                  |
| EC <sup>1</sup> |                                                                                 | (mS/cm) |                                                                            |                  |                                   |                                  |
| TDS             |                                                                                 | mg/L    |                                                                            |                  |                                   |                                  |
| CN-Free         |                                                                                 |         |                                                                            |                  |                                   |                                  |
| WAD-CN          |                                                                                 |         |                                                                            |                  |                                   |                                  |
| CN-Total        |                                                                                 |         |                                                                            |                  |                                   |                                  |

Note 1: In-field non-NATA accredited analysis permitted.

## Time limited operations phase

### Commencement and duration

8. The works approval holder may only commence time limited operations for an item of critical containment infrastructure identified in condition 10:
- (a) where the CEO has notified the works approval holder that the Critical Containment Infrastructure Report for that item of infrastructure as required by condition 5 meets the requirements of that condition.
  - (b) Where at least 45 business days have passed after the Critical Containment Infrastructure Report for that item of infrastructure as required by condition 5 has been submitted to the CEO.
9. The works approval holder may conduct time limited operations for an item of

infrastructure specified in condition 10 (as applicable):

- (a) for a period not exceeding 180 calendar days from the day the works approval holder meets the requirements of condition 8 for that item of infrastructure; or
- (b) until such time as a licence for that item of infrastructure is granted in accordance with Part V of the *Environmental Protection Act 1986*, if one is granted before the end of the period specified in condition 9(a).

### Time limited operations requirements and emission limits

10. During time limited operations, the works approval holder must ensure that the premises infrastructure and equipment listed in Table 5 and located at the corresponding infrastructure location is maintained and operated in accordance with the corresponding operational requirement set out in Table 5.

**Table 5: Infrastructure and equipment requirements during time limited operations**

|    | Site infrastructure and equipment                   | Operational requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Infrastructure location                          |
|----|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| 1. | Fimiston III TSF                                    | <ul style="list-style-type: none"> <li>Minimum freeboard of 300 mm.</li> <li>Decant pond of no more than 15% of basin area of Fimiston III TSF during normal operating conditions.</li> <li>In the event that the size of the supernatant pool becomes greater than the target size (e.g. due to a high rainfall event), decant water from the TSFs will be used as a priority for mineral processing in preference to groundwater derived from remote saline water borefields.</li> <li>Underdrainage</li> <li>When deemed necessary, seepage recovery bores are to be installed as per condition 4 and to the design and construction / installation requirements in Table 3.</li> </ul> | As located in Schedule 1, Figure 1 and Figure 2. |
| 2. | Pipelines carrying tailings and decant return water | <ul style="list-style-type: none"> <li>Equipped with automatic cut-outs in the event of a pipe failure; or</li> <li>Provided with secondary containment sufficient to contain any spill for a period equal to the time between routine inspections.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                  |

11. The works approval / licence holder must manage dust generation at the premises by:
  - (a) wetting down unsealed roads and exposed areas with a water truck.
  - (b) limiting all vehicle traffic within the premises to speeds of less than 40 km/hr; and
  - (c) ceasing dust-generating activities during strong wind conditions.

### Time limited operations – authorised discharge points for emissions

12. During time limited operations, the works approval holder must ensure that the emission(s) specified in Table 6, are discharged from the corresponding discharge point(s) and at the corresponding discharge point location(s).

**Table 6: Authorised discharge point**

|    | Emission | Discharge point  | Discharge point location           |
|----|----------|------------------|------------------------------------|
| 1. | Tailings | Fimiston III TSF | As located in Schedule 1, Figure 1 |

### Monitoring during time limited operations

13. The works approval holder must monitor the groundwater during time limited operations for concentrations of the identified parameters in accordance with Table 7.

**Table 7: Monitoring of ambient concentrations during time limited operations**

| Parameter       | Monitoring location                                                             | Unit    | Frequency | Averaging period | Method                            |                                  |
|-----------------|---------------------------------------------------------------------------------|---------|-----------|------------------|-----------------------------------|----------------------------------|
|                 |                                                                                 |         |           |                  | Sampling                          | Analysis                         |
| SWL             | All proposed monitoring bores as established under condition 2 of this licence. | m bgl   | Quarterly | Spot sample      | In accordance with AS/NZS 5667.11 | In accordance with AS/NZS 5667.1 |
| pH <sup>1</sup> |                                                                                 | -       |           |                  |                                   |                                  |
| EC <sup>1</sup> |                                                                                 | (mS/cm) |           |                  |                                   |                                  |
| TDS             |                                                                                 | mg/L    |           |                  |                                   |                                  |
| CN-Free         |                                                                                 |         |           |                  |                                   |                                  |
| WAD-CN          |                                                                                 |         |           |                  |                                   |                                  |
| CN-Total        |                                                                                 |         |           |                  |                                   |                                  |

Note 1: In-field non-NATA accredited analysis permitted.

14. The works approval holder must record the results of all monitoring activities required by condition 13.

### Compliance reporting

15. The works approval holder must submit to the CEO a report on the time limited operations within 60 calendar days of the completion date of time limited operations or 60 calendar days before the expiration date of the works approval, whichever is the sooner.
16. The works approval holder must ensure the report required by condition 15 includes the following:
- (a) a summary of the time limited operations, including timeframes and amount of tailings discharged; and
  - (b) a summary of monitoring results obtained during time limited operations under condition 13.

### Records and reporting (general)

17. The works approval holder must record the following information in relation to complaints received by the works approval holder (whether received directly from a complainant or forwarded to them by the department or another party) about any alleged emissions from the premises:

- (a) the name and contact details of the complainant, (if provided).
  - (b) the time and date of the complaint.
  - (c) the complete details of the complaint and any other concerns or other issues raised; and
  - (d) the complete details and dates of any action taken by the works approval holder to investigate or respond to any complaint.
- 18.** The works approval holder must maintain accurate and auditable books including the following records, information, reports, and data required by this works approval:
- (a) the works conducted in accordance with condition 1.
  - (b) any maintenance of infrastructure that is performed in the course of complying with condition 10.
  - (c) monitoring programmes undertaken in accordance with conditions 7, 10, 13; and
  - (d) complaints received under condition 17.
- 19.** The books specified under condition 18 must:
- (a) be legible;
  - (b) if amended, be amended in such a way that the original version(s) and any subsequent amendments remain legible and are capable of retrieval;
  - (c) be retained by the works approval holder for the duration of the works approval; and
  - (d) be available to be produced to an inspector or the CEO as required.

## Definitions

In this works approval, the terms in Table 8 have the meanings defined.

**Table 8: Definitions**

| Term                                       | Definition                                                                                                                                                                                                                                                                          |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| books                                      | has the same meaning given to that term under the EP Act.                                                                                                                                                                                                                           |
| CEO                                        | means Chief Executive Officer.<br>CEO for the purposes of notification means:<br>Director General<br>Department administering the <i>Environmental Protection Act 1986</i><br>Locked Bag 10<br>Joondalup DC WA 6919<br><a href="mailto:info@dwer.wa.gov.au">info@dwer.wa.gov.au</a> |
| critical containment infrastructure        | means the items of infrastructure listed in condition 1.                                                                                                                                                                                                                            |
| Critical Containment Infrastructure Report | means a report to satisfy the CEO that works of critical containment infrastructure have been constructed in accordance with the works approval.                                                                                                                                    |
| Department                                 | means the department established under section 35 of the <i>Public Sector Management Act 1994</i> and designated as responsible for the administration of Part V Division 3 of the EP Act.                                                                                          |
| discharge                                  | has the same meaning given to that term under the EP Act.                                                                                                                                                                                                                           |
| emission                                   | has the same meaning given to that term under the EP Act.                                                                                                                                                                                                                           |
| Environmental Compliance Report            | means a report to satisfy the CEO that the conditioned infrastructure and/or equipment has been constructed and/or installed in accordance with the works approval.                                                                                                                 |
| EP Act                                     | <i>Environmental Protection Act 1986</i> (WA).                                                                                                                                                                                                                                      |
| EP Regulations                             | <i>Environmental Protection Regulations 1987</i> (WA).                                                                                                                                                                                                                              |
| KCGM                                       | The works approval holder, Kalgoorlie Consolidated Gold Mines Pty Ltd                                                                                                                                                                                                               |
| monthly period                             | means a one-month period commencing from [day X] of a month until [day (X-1)] of the immediately following month.<br><i>e.g. "means a one-month period commencing from the seventh day of a month until the sixth day of the immediately following month."</i>                      |
| premises                                   | the premises to which this licence applies, as specified at the front of this licence and as shown on the premises map (Figure 1)                                                                                                                                                   |

| Term                                     | Definition                                                                                                                                                                                                                                                                                                                   |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                          | in Schedule 1 to this works approval.                                                                                                                                                                                                                                                                                        |
| prescribed premises                      | has the same meaning given to that term under the EP Act.                                                                                                                                                                                                                                                                    |
| suitably qualified geotechnical engineer | means a person who: <ul style="list-style-type: none"> <li>• holds a Bachelor of Engineering recognised by the Australian Institute of Engineers; and</li> <li>• has a minimum of five years of experience working in geotechnical engineering including experience in the design of tailings storage facilities.</li> </ul> |
| time limited operations                  | refers to the operation of the infrastructure and equipment identified under this works approval that is authorised for that purpose, subject to the relevant conditions.                                                                                                                                                    |
| waste                                    | has the same meaning given to that term under the EP Act.                                                                                                                                                                                                                                                                    |
| works approval                           | refers to this document, which evidences the grant of the works approval by the CEO under section 54 of the EP Act, subject to the conditions.                                                                                                                                                                               |
| works approval holder                    | refers to the occupier of the premises being the person to whom this works approval has been granted, as specified at the front of this works approval.                                                                                                                                                                      |

---

**END OF CONDITIONS**

# Schedule 1: Maps

## Premises map

The boundary of the prescribed premises is shown in the map below (Figure 1).




Figure 1: Map of the boundary of the prescribed premises




Figure 2: KCGM pipeline corridor between processing plant and TSFs




Figure 3: Fimiston III TSF embankment design (Cell 1 and 2)




Figure 4: Fimiston III TSF embankment design (Cell 1 and 3, and Cell 2 and 3)




Figure 5: Fimiston III TSF underdrainage design




Figure 6: Fimiston III TSF proposed monitoring bore indicative locations